ERVIN WILNEDER

Business factories

How to organize and run a business that works with artificial intelligence

FIRST EDITION · NOVEMBER 2026

Contents

Prologue 4
Part I. The idea 6
1. A business as a business factory 7
2. Knowing and doing 10
Part II. How it is organized 13
3. Roles, people, and access 14
4. Conversations: how a role works 17
5. What a role knows 22
6. Work as a record 25
7. Connections and a single door 29
8. Work that runs on its own 32
Part III. How it is governed 35
9. Ceiling and judgment 36
10. Can it be undone without anyone noticing? 41
11. Five forms of message 45
12. How a request comes in 49
Interlude. A day at Ópticas Horizonte 51
Part IV. How it is built 53
13. The machine behind each business factory 54
14. The work in git 58
15. Connections from the inside 61
16. Folders and *blueprint* 64
Part V. Directing 67
17. Directing instead of doing 68
18. Cost and quality 71
19. Typical failures and what stops them 74
20. How a business factory improves 77

Epilogue. What is still unresolved 80
Appendix. Build it: a guide for your agent 82
References 98
Glossary 99

Prologue

This book is about **how a business is organized when part of its work is done by artificial intelligence agents**. It is not a manual for a tool, nor a promise about the future: it is the description of a model, with its parts, the reasons behind each one, and what is still unresolved.

The starting point is a distinction worth making early. When people talk about agents working as a team, the usual picture is a *software factory*, where agents write code, open changes, and someone reviews them. The model in this book is a different one: **a *business factory***, where agents fill the roles of a company (sales, administration, purchasing) and their work is the work of the business itself. In a *business factory*, there is no need to review every change as if it were code, and the question that matters is a different one: who decides what.

From that question come the three ideas that run through the book.

The first is that people direct and agents do. Whoever runs a business should not have to understand how the *business factory* works inside, and the goal is for **people to have as little contact as possible with technical matters**. This does not mean the technical side is unimportant, only that its place is elsewhere: to hold up, without drawing attention to itself, an arrangement in which each person knows whom to ask for things and each agent knows what is its to do.

The second is that structure matters more than the intelligence of each agent. A very capable agent, without a clear role, without a place to keep its work, and without rules about whom it talks to, quickly produces results that are hard to follow. A good part of the book is devoted to that structure: roles, conversations, levels of knowledge, connections, routines.

The third is that control rests on a few firm limits and a great deal of judgment. Faced with the temptation to require an approval for every action, the model chooses the opposite: fewer approvals, which tend to add

more noise than control, and **roles that decide for themselves whom to ask before acting**. What is not negotiable is the ceiling on what each one can do; the rest is left to each role's judgment. It is a decision with risks, and the book names them.

It should be noted that none of this was thought up in the abstract. Every decision described here came out of building and operating a real *business factory*, with its mistakes and its corrections. The examples, on the other hand, use an invented business (Ópticas Horizonte, a chain of three optical stores that sells eyeglasses) and, from time to time, an independent accountant, so that the ideas can be seen in motion without depending on any particular case.

The book is meant for three readers. For whoever runs a business, or for an independent professional in any field who wants a team of agents working with them and for them, and wants to understand what changes if part of the work is done by agents, and what remains theirs. For whoever researches how agent systems are organized and is looking for decisions with their reasons, and also for what was left open. And for whoever wants to know how the person who built a system thinks.

The next chapter presents the idea of a *business factory* and its main parts.

License

The text of this book is published under the Creative Commons Attribution 4.0 International (CC BY 4.0) license: it may be copied, adapted, and shared, including for commercial purposes, provided the source is credited. Third-party works cited keep their own licenses.

Part I. The idea

1. A business as a business factory

A ***business factory*** is the set of artificial intelligence agents of a business (or of an independent professional's practice), together with the place where they work and the rules that order that work. Each business has its own, each person in the business works in **their own copy** of it, and what gets built there belongs to the business and to no one else.

The word *factory* is not accidental. A real factory is not a collection of loose machines: it is a place where each station has its function, material moves along known paths, and the result can be traced from end to end. That is precisely the difference from the most common way of using artificial intelligence in a company, where each person talks with an assistant on their own and whatever comes out of those conversations stays scattered.

Roles, not assistants

The basic part of a *business factory* is the **role**. A role is a position in the business («Sales», «Administration», «Purchasing») always filled by an agent. It has its instructions, what it knows how to do, the systems it can reach, and the work that runs on its own.

The reason to think in roles rather than assistants is practical. A single agent that does everything gets confused and is hard to correct: when something goes wrong, it is not clear which instruction failed. With roles, **each agent has a clear job, just like a department in a company**, and each correction has a place to be applied.

A business, or one person's practice

Everything this book says about a business also holds for **an independent professional in any field**: a lawyer, a designer, a consultant, an accountant, a researcher. Their practice is their business, and it can have a team of

agents working **with them and for them**, each in one area of their work. The word *business* in the term does not change: what changes is the scale.

> **Example.** Besides Ópticas Horizonte, the book returns from time to time to a second case: an independent accountant with a handful of regular clients. Her *business factory* has three roles: Clients (queries and requests for documents), Payroll and Taxes (each month's calculations), and Deadlines (what falls due and whom to notify). She is the only person.

The coordinating role and the leaders

The roles of a *business factory* are not all alike. At the top there is **a coordinating role**: it sees everyone's work, distributes what crosses areas, and decides which role takes each new request. In each person's copy, that role is the ***owner***: the conversation through which that person comes in.

Below are the **leaders**, the roles at the first level. In a small *business factory*, every role in the business is a leader; nothing prevents there being more levels someday (and that is why it is best not to define a leader as «any role other than the coordinating one», even though today the two coincide).

> **Example.** In Ópticas Horizonte, General Management is at the top. Below it are three leaders: Sales, Administration, and Purchasing.

What belongs to every business factory and what belongs to each business

There is a second separation, less visible and just as important as the first. One part of how a *business factory* works is **the same for every business**: what kinds of conversation exist, how roles hand work to one another, where finished work is kept. Another part is **specific to each business**: what roles it has, what they know, which systems they work with.

What is common is defined only once, in a versioned *blueprint*, and what is specific to each business lives apart. The separation has to be sharp, so that every *business factory* can be improved **without affecting what each business defined**. The idea is not new: other industries call it *standard work* (lean manufacturing), *process of record* (chip fabrication), or *master recipe* (the ISA-88 standard).

What matters, in the end, is that **whoever improves the *business factory* and whoever runs the business work on different things** and do not step on each other.




Figure 1: The coordinating role, the leaders, and what is specific to each business, kept apart from what is common to every *business factory*.

The people

A *business factory* does not replace the people of the business: it arranges them differently. **Each person has their own copy of the *business factory***: they come in through their own conversation with the coordinating role (the *owner* of their copy) and from there reach only the roles they were given access to.

Whoever buys from the business, by contrast, is not a person of the *business factory*. An end customer never has a conversation with a role; they are served through the business's channels, as chapter 8 will show.

To recap, a *business factory* has roles filled by agents, a coordinating role with leaders below it, a part common to every *business factory* and a part specific to each business, and one copy per person, with only the roles that person has access to. The next chapter looks at the separation that holds up everything else: the one between what the business is and what its agents do.

2. Knowing and doing

The architecture of a business factory rests on a separation: **on one side, the definition of what the business is; on the other, the execution of what its agents do**. The first describes; the second works. Neither replaces the other.

The business definition

The **business definition** is the record of how the business operates: what roles it has, what work each one does, with which tools, with what knowledge, and how far it is from its goals. It has no people and no conversations: it only describes.

That record is **the source of truth**. When a conversation starts, it reads from there what its role knows and what it can do; when someone changes an instruction, they change it there, and from that moment on every conversation of the role sees it the same way.

Execution

Execution is the business factory at work: the agents, each in its role, conversing, thinking, and acting. A coordinating component reads the business definition and assembles the business factory according to it (which conversations exist, what falls to each one), and the conversations run on a machine of the business's own, isolated from the others, which goes to sleep when there is nothing to do and wakes up when a message arrives or something falls due.

The shift this implies is worth pointing out. In a first version of this kind of system, it is usually the same service that thinks for the agents and stores everything else. In this model, the coordinator **stops thinking and starts coordinating**: it decides which conversation has to answer what, and the thinking happens on the business factory's machine, with an artificial intelligence engine that each business chooses.

Why separate them

The main reason is the pace of change. What a business *is* changes little and is decided by a person; what its agents *do* happens all the time, conversation by conversation. If both lived together, **any conversation could rewrite the business**, by mistake or through a malicious text that came in from outside.

Kept apart, each one has its own rules:

	Business definition	Execution
What it holds	roles, knowledge, connections, goals	conversations, turns, work in progress
Who changes it	people with access for that, or their conversations when they ask for it	the agents, all the time
What happens if execution is erased	nothing of the business is lost	it is reassembled from the definition

The last row is perhaps the most important. **A business factory can be destroyed and brought back up without losing anything of the business**, because everything that matters lives in the definition or in each role's saved work (chapter 6), and never only in a conversation's memory.

> **Example.** In Ópticas Horizonte, the business definition says there is a role «Sales», that it follows the skill «How to put together a quote», and that its goal is to close 120 sales a month. When someone writes to Sales, the business factory reads that, and only then does the agent answer. If tomorrow the business factory's machine is replaced by another one, Sales still knows exactly the same things.

A small core and extensions

The same logic applies to the rest of the system. What has to be always on (people's identity, the business definition, the coordination of the agents, the event wire between services, and spending control) forms a small, stable **core**. Everything else (a customer tracking system, a document archive, mechanical processes, integration with a messaging platform) comes in as an **extension**.

The rule runs one way only: **the core never depends on an extension to work**; extensions, on the other hand, can use the core. Extensions add capabilities to the core; they do not replace it.

To recap, the business definition knows and the business factory does; the first is the source of truth and the second can be rebuilt from it. With that separation as a base, Part II goes through how work is organized inside the business factory.

Part II. How it is organized

3. Roles, people, and access

A **role** is a set of instructions, always an agent's, tied to what it knows how to do, the systems it reaches, the channels it serves, and the work that runs on its own. It has a name, a description, and, optionally, the artificial intelligence model it uses.

A name that does not change

Each role is identified by a fixed internal name. Its title can change («Sales» can be renamed «Commercial»), but that internal name cannot, and an archived role keeps it forever without any other role being able to take it.

It looks like a detail, but it is not. If a role's name could be reused, **what was given to one role (its permissions, its connections, its history) could pass to another by accident**. An identifier that is never recycled prevents that kind of error by design.

Role is not access

Two words that are often confused are worth telling apart.

- **Role** is what an agent does: «Sales» answers inquiries and puts together quotes.
- **Access** is what a person can do in the business. There are usually three levels: whoever can configure everything (admin), whoever can change what belongs to the roles within their reach (*manager*), and whoever works with their role and handles their own things (collaborator).

A person having access to a role (seeing it in their copy and asking it for things) does not make them the agent. The role is always filled by an agent, and the person directs it.

Each person, their own copy

In this model, **each person has their own copy of the business factory**. They always come in through the same place, their own conversation with the

coordinating role (the *owner* of their copy), and from there reach **only the roles they were granted access to**. A person can have access to one role or to several; a role can be in the copies of several people.

The alternative (a single shared business factory, which every person enters through the same door) looks simpler, and in a first version it is usually what gets built. The problem shows up with use: conversations from different people get mixed in the same roles, what one person asked for is visible to another, and it is hard to separate what each role is doing for whom. With one copy per person, **each person has a door of their own that they know**, sees only what concerns them, and the coordinating role in their copy takes care of distributing what they ask for among the roles they have access to.

Those who administer the business usually have access to every role; everyone else, to the roles of their area.

When there is only one person

For an independent professional, the model becomes simpler without changing shape:

- there is **a single copy**, theirs, and they always come in through their *owner* conversation;
- the person has **admin access**: they are the one who defines the roles, their rules, and what gets approved;
- **the roles are their own areas of work**, not departments of a company;
- approvals, the five message forms, and the record of the work serve just the same: the record tells them what they decided and when, and the *owner* asks them only what needs them.

> **Example.** The independent accountant comes in through her *owner* and asks it to prepare the month's payroll and tax calculations. The *owner* passes it to Payroll and Taxes, which works with the data that Clients gathered during the week. When Deadlines detects that a client has a payment due on Friday, it sends that to the *owner*, and the *owner* tells her along with everything else that needs her that day.

Access is the ceiling

The access of each conversation works as **a ceiling that nothing goes above**. What the person cannot do, an agent in their conversation cannot do either; no instruction, skill, or memory raises it.

Conversations that belong to no person (the ones the next chapter covers) carry the narrowest access of all, that of a collaborator. The reason is simple: **what runs without a person in front of it should not be able to do more than the most limited of those who work in the role**. What only an admin can do is done by an admin, or by an admin's conversation when the admin asks for it.

> **Example.** The salesperson at Ópticas Horizonte is a collaborator. They ask their role to change the general instruction on discounts. The agent cannot: that change belongs to an admin, and the person's ceiling is the agent's ceiling. What it can do is pass the request on to the proprietor.

Who talks to whom between roles

Roles hand work to one another, but in an order:

- the coordinating role can write to any leader;
- a leader can always write to the coordinating role;
- two leaders can write to each other directly, but only for a question or its answer;
- **a new request for another area always goes through the coordinating role**, which decides whose it is.

The distinction between a question and a request is deliberate. A quick question needs no intermediaries; a new request is work that someone has to prioritize, and prioritizing belongs to whoever coordinates.

In short, a role belongs to an agent and each person works in their own copy, with the roles they have access to; access is the ceiling and is never negotiated; and roles pass questions to each other directly, but requests through whoever coordinates. The next chapter looks at how work is divided within each role.

4. Conversations: how a role works

In a business factory, all work happens in **conversations**, and each conversation always belongs to a role. What distinguishes one from another is what it exists for, whom it works for, and who sees it.

One copy per person, one body of work per role

Each person has their own copy of the business factory (chapter 3), and the conversations in that copy **answer to that person**. But the work is not copied: **each role keeps a single body of work per business**, the same no matter which person a conversation is answering (chapter 6).

It is the combination of the two that makes the model work. The copy separates *for whom* the work is done: what one person asks for does not get mixed with what another asks for. The shared work keeps the area from splitting into as many versions as there are people: if each copy kept its own work, each person would see a different area. **What crosses from one person to another goes through that shared work**, not through conversations talking to each other across copies.




Figure 2: Each person works in their copy, with their roles; each role's work is a single one for the whole business.

Four kinds of conversation

Conversation	What it exists for	Whom it works for
owner	it is the person's door to their copy: it receives their requests, distributes them among the roles they have access to, and answers them	the person of that copy
a role's main conversation	it does the role's work and keeps it in the role's work	the person of that copy, on the work of the whole business
routine	it carries out a routine each time one is due (chapter 8)	the role, not a person
task	it does a piece of work that has an end, and closes when it finishes	whoever opened it

The *owner* conversation

The *owner* conversation is **the only place through which a person comes in**. What it can resolve there it resolves there (a question about the status of something, a piece of data from a role's saved work); what belongs to an area it passes to the corresponding role, and it comes back with the answer.

The order of the answer is also deliberate. First, quickly, whatever can already be answered. If the request needs a role, that is said in one line before going to get it, and then the full answer arrives. **No request is left unclosed.**

It is also **the only conversation that asks the person anything**. When a role needs a decision, it does not ask the person directly: it sends the *owner* what it needs, with a recommendation, and the *owner* gathers those needs and presents them to the person (chapters 9 and 11). The person, in this way, always answers a single counterpart.

> **Example.** The salesperson asks their *owner* how many quotes they have pending, and the answer comes right away, read from the work of Sales. Then they ask for a quote with financing for a customer: the *owner* says it will put it together with Sales and bring it back, passes it to Sales' main conversation in their copy and, when it is ready, shows it to them. The quote stays in the work of Sales, where the proprietor also sees it from her own copy.

Tasks and routines, each apart

When a piece of work with an end would take up so much of a conversation that it would stop attending to everything else, a **task** is opened: a separate conversation that does that work, reports the result, and closes once the result is saved.

Routines follow the same logic, with a single difference. Tasks and routines are delegations, and the only thing that really distinguishes them is time: a task ends, a routine comes back each time it is due. That is why **each routine always runs in its own conversation**, and since it belongs to the role and not to a person, what it produces goes straight into the role's work.

Subagents

A **subagent** is something else: a short-lived helper, with no role, that a conversation creates for a specific job (researching, comparing, reviewing).

It starts **without the context** of whoever created it, receives complete instructions, and returns a report. It asks nobody anything and does not write to other conversations.

The lack of context is deliberate. A subagent that did not see the conversation does not inherit its assumptions, and that is why it is useful, for example, for reviewing with fresh eyes what the conversation did.

The rule of who talks to whom

- Within a copy, routines and tasks talk **only with their role's main conversation**, and the roles' main conversations cross paths through the *owner*, except for direct questions between leaders (chapter 3).
- Between copies, nobody talks: **what has to get from one person to another stays in the role's work**, where the other person finds it.

It is a traffic rule, and like every traffic rule it restricts in order to bring order: **each request comes in through one place and goes out through one place**, and nobody works on something the area does not know exists.

To that rule a brake is added. There is a maximum number of consecutive turns without a person in between; a person's message, or a routine's run, resets the count. It is the protection against the simplest failure of multi-agent systems: **two agents handing work back and forth without end**.

Turns, deliveries, and questions

Each conversation works in **turns**: one run of the agent that answers exactly one **delivery** (a person's message, a routine's notice, a task's result, a message from another role). A conversation receives deliveries one at a time.

When a conversation is missing a decision, **it does not guess**: it asks the *owner* for it, with options and a recommendation, and waits. If what it is about to do cannot be undone, it says so with a mark (which is a warning, not a brake: the person answers as they would any message).

Finally, those who direct a role can see what its routines and tasks are doing, and **pause them** with a single action, without going through a conversation. The pause is immediate, and who made it is recorded.

To recap, each person comes in through the *owner* conversation of their copy, which is also the only one that asks them anything; each role keeps a single body of work for the whole business; and tasks and routines run

apart, ordered by a simple traffic rule. The next chapter looks at what each of those conversations knows.

5. What a role knows

A role's **knowledge** is everything that tells it how to behave and how to do its work. It is made of three kinds of piece (instructions, *skills*, and memories), and each piece lives at a **level**, which says whom it applies to.

Three levels

Level	Applies to
business	every role
role	that role, in all its conversations
person	that person, in their conversation

The levels **do not form a hierarchy**. They go from the broadest to the narrowest, but none overrides another: role and person are two dimensions that cross in each person's conversation. A piece's level is chosen when it is created and does not change.

The reason for having levels is to avoid contamination. Some things belong to the whole company («all customers are addressed on a first-name basis»), others to a job («this is how a quote is put together»), and others to a person («prefers short answers»). **Mixing them in a single pile makes the personal end up in the general**, and someone's preference becomes, without anyone meaning it to, a rule for everyone.

When two pieces clash

The agent receives the **sum** of the levels that apply to it, and no level wins by rule. If two instructions contradict each other, the agent decides with judgment and, if asked, explains why. The healthy thing, when that happens, is for a person to correct the instruction that is wrong.

It might seem tidier to set a priority (the person wins over the role, the role over the business). There is a case for the opposite view: **a fixed priority rule**

works in the common cases and fails in the rare ones, which are precisely the ones that matter. It is better for the agent to reason and for people to fix the source of the clash.

Instructions and skills

An **instruction** says *how to be*: «always speak on a first-name basis, and never promise delivery dates without checking with the workshop». A **skill** says *how to do one concrete thing*, and the agent reads it only when it needs it. Skills are usually of three kinds:

- those that explain **how to use a tool** (its map, how to get in, the common tasks and their pitfalls);
- those that explain **how this business does a type of work** with its tools;
- those that say **what to do when something fails** or a person is needed.

The skills the business writes live in the business definition, at its three levels. Those that say how every business factory works (how roles hand work to one another, how finished work is kept) are part of the *blueprint*, and they are updated without touching the business's own.

Memory: each level written by its own

A **memory** is a fact about how to behave that a conversation saves for later. It is written **without asking for confirmation**, and stays in view, with its history, so that a person can correct it or undo it.

Who writes each level is fixed, and each level is written by its own:

Level	Written by
role	the role's main conversation, in any copy
person	that person's *owner* conversation
business	the *owner*, and only in the copy of someone who has access to change what belongs to the business

Routines and tasks do not write memory. What they learn about the work stays in the role's work (chapter 6).

Memory is not work. Memory keeps how to behave («the proprietor likes one-page reports»); the state of what is being done («yesterday's customer quote is on its second version») goes into the role's work. The distinction keeps memory from filling up with data that goes stale in days.

Memories are not orders. They are presented to the agent as notes, with who wrote them and when, and the agent treats them as data. A memory that looks like an order is not followed as one, and this matters more than it seems: it is one of the doors through which a malicious text could try to take up residence in an agent system.

What is always loaded, kept short

There is a part of the knowledge that every conversation reads when it starts: the common rules, the business's instructions, and the role's. That part should be **short**. Every line that is always loaded is paid for in every conversation, and a long text that nobody rereads ends up being noise (chapter 19).

The practice that works is simple: what always applies stays in what is always loaded; the history of why something was decided, the quotes, and the dates go to a separate record that is consulted when needed; and what belongs to a single role goes into that role's knowledge, not everyone's. A glossary, for example, is consulted when a doubtful term comes up, instead of being read in full every time.

What knowledge never does

Knowledge **informs, but does not authorize**. An instruction that says «customers can be deleted without asking» does not raise anyone's ceiling. The ceiling is access (chapter 3), and it holds firm whatever the knowledge says.

In short, knowledge lives at three levels that add up without a hierarchy, each level is written by whoever it belongs to, and nothing that is known widens what can be done. The next chapter looks at where what each role does is kept.

6. Work as a record

A **role's work** is what the role has done and has in progress: the quotes it put together, the reports, the plans, the status of each open request. It is kept in the role's own place, with its complete history.

Nothing important lives only in a conversation

The idea that organizes this chapter is short: **a conversation can be closed or restarted at any moment, and the work has to outlive it**. Agents' conversations have a limit on what they can remember, they are compacted when they grow, and they are restarted when the version of the business factory changes. If the work lived in them, each of those events would be a loss.

That is why all of a role's conversations (the main one, the task conversations, and the routine conversations), **in any person's copy**, work on the same record, and each one leaves there what it produces. Each role keeps a single body of work per business, no matter which person a conversation is answering. The alternative, in which each conversation, or each copy, carries its own version of the work, was ruled out early: **copies that diverge while the work is running** are the source of almost every conflict.

A record with history

The record of the work is kept the way a development team keeps its code: **every change is saved with who made it and when**, and it is possible to see the difference from the previous version or to go back. But it is not used with the ritual of software development (branches, reviews of every change): in a business factory, each role saves directly onto the main version.

The choice has an advantage that is not obvious at first. A record with history **turns trust into something verifiable**: when a role says it did something, one can look at what changed, and when something goes wrong, it can be undone without depending on anyone's memory.

Few conflicts by design

When several conversations write to the same place, the risk is that they overwrite each other. Three simple rules reduce it:

- **one file per thing** (a request, a record, a plan), never one large shared file;
- fetch the latest before starting, and save as soon as the work is finished, in small changes;
- if two changes are incompatible, **nothing is overwritten**: one's own version is saved apart, and whoever decides which one stays is notified.

> **Example.** At Ópticas Horizonte, Sales' main conversation keeps each quote in its own file. A follow-up routine notes in that same file that the customer received the reminder. The salesperson, from their copy, reads the updated status without anyone telling them, and the proprietor, from hers, sees the same file.

Work, knowledge, and files

It is worth closing with the three things a business factory keeps that are often confused:

What	Where	Example
how the work is done	knowledge, in the business definition	the skill «How to put together a quote»
what was done and is in progress	the role's work, with history	yesterday's customer quote
the files shared with people	the business factory's file archive	the PDF that was sent to the customer

Starting each day from a note

Having the work live outside the conversations allows something more: **starting each day with a new conversation**. Before stopping, each conversation leaves a short note in its role's work: what it was doing, what the next step is, what remains open, what it expects from others and what it owes, and what it did not get to verify. The next day, only the roles that have something pending start, and they start from that note, not from yesterday's conversation.




Figure 3: The cycle of a conversation: from the day's note to the turn, to the commit, and back to the note.

The alternative (continuing the same conversation day after day) looks more convenient, but it accumulates context that is no longer useful and that is paid for on every turn. A well-written note carries what matters and leaves the rest behind.

Each role's data

Some roles work with data in table form (customers, transactions, readings from a system), and for that data a record of text files is not enough. One way to solve this is to give each role **a data store of its own**: a local database in which the role works, synchronized with a central copy that a service keeps. The role fetches the central copy, works, and uploads only what changed.

Three rules make it work with several conversations at once:

- **each table has a single owning role**, the only one that writes to it; the others read it;
- each table declares what identifies each row, so that changes can be compared row by row;
- if another conversation changed the same row in the meantime, **the change is not overwritten**: it is set aside for whoever arrived second to review.

The last rule comes from a concrete test: with the opposite rule (the last one to write wins), a change was lost without anyone noticing. And the idea of keeping these tables with the same system that keeps the text files was also ruled out, because data files cannot be merged when two people change them at the same time.

To recap, the work lives in a record with history that all of the role's conversations share, and that is why no conversation is indispensable. The next chapter looks at how agents reach the business's systems.

7. Connections and a single door

A **connection** is the way an agent reaches a system: email, the calendar, the management system, a spreadsheet. Without connections, an agent can only talk; with them, it can look at real data and act.

The role's and the person's

Connections come in two kinds, and the difference between them is one of the central decisions of the model:

- a **role connection** belongs to the role, and is used by its main conversation, its routines and its tasks;
- a **personal connection** belongs to a person (their email, their account on a service), and is used **only in that person's copy, and only when they ask for something that needs it**.

The rule fits in one sentence: the role's connections are for the whole role; a person's are used only in their copy and when they ask. Behind it is a fairly intuitive idea of ownership. A person's email is theirs: there is no reason for the whole area to read it, or for a routine that runs at night to go into that mailbox. **What belongs to the role is used by the role; what belongs to each person is used only by that person, when they ask.**

Connecting something of one's own, moreover, is always done by the person, never by an agent: an agent can point out where it is done, but the act of connecting, changing or deleting a connection belongs to the person.

Credentials never reach the agent

The access keys to each system **do not live in the database of the business definition or on the business factory's machine**. They live in an encrypted vault, with a space of its own for each business, from which they cannot be

read back: they can only be used to call the service. A person's connection to an outside service, in turn, is made in the person's own browser, through the service's own flow, so that **the system never sees their password**.

The goal is that if someone one day gains access to the database or to the business factory's machine, they will not find a single key. And there is a second goal, specific to agent systems: an agent that never sees a credential **cannot leak it**, whether by mistake or because a text from outside persuaded it to.

A single door

Every call the agents make to the business's systems goes through **a single gateway**. Each conversation receives an address of its own that shows it only what concerns it (its role's connections and, if the person asked, that person's), and it is the gateway that calls the service with the right credential.

The reason for concentrating everything in one door is operational. With a single door, **one can see in one place who called what, and cut it off in one place** if something goes wrong. Organizations that connect hundreds of agents to hundreds of systems tend to reach the same conclusion: a central gateway, not one cable per agent.

Limits within each connection

Each connection can also **restrict** which operations the agent may use (a list of what is allowed) and **fix** certain values so that the model does not make them up.

> **Example.** At Ópticas Horizonte, Sales has a connection to the stores' appointment system. It can only look up appointments and create one; it cannot delete. The store's identifier is fixed in the connection, so the agent cannot get the branch wrong.

What has no way to connect

Some systems offer no way to connect through software. For those cases, the model uses a **remote browser**: the person logs in once, by hand, in a live view that only they can see, and the agent then works with that login, browsing with a copy that does not keep changes. It is a compromise (slower and more fragile than a direct connection), but it covers what would otherwise be left out.

Outfitting a connection

Connecting a system is not the same as knowing how to use it. For the most important systems, especially those that can only be reached through a browser, an intermediate step is worthwhile: **test the connection thoroughly first, and outfit it afterwards**.

The test goes through the system for real: what can be read, where each piece of data is, what fails. With what was learned, a **loadout** is put together for the role:

- **read tools**, each one validated against the real system before it is accepted;
- **proposed write tools**, which stay as proposals until a real business case that needs them comes up;
- **skills** that explain how to use that system and how this business uses it;
- **routines** that read what matters and give notice only when something has really changed.

The asymmetry between reading and writing is deliberate. Reading badly produces a wrong piece of data that can be corrected; writing badly can change something in an outside system. **First one explores and validates, and only then builds on solid ground.**

One tool, one guide

Each connection can be linked to the skill that explains how to use that system: its map, its common tasks, its pitfalls. **Connection and guide go together**, because an agent that can get into a system but does not know how to move around in it tends to do more harm than one that cannot get in.

To recap, the role's connections belong to the role and each person's belong only to that person; credentials live beyond the agents' reach; and everything goes through a single door. The next chapter looks at the work that runs without anyone asking for it.

8. Work that runs on its own

A good part of a business's work does not start with a person asking for something: it starts when the time comes or when something happens. That is what **routines** are for, along with the **events** that wake them, the **channels** through which people outside are served, and **reminders**.

Routines

A **routine** is a process carried out by an agent, for work that is complex or calls for judgment. It has a purpose, steps and a definition of «done», and a role carries it out when its trigger fires.

A routine wakes up **on a schedule** («every business day at 9», with a time zone) **or on an exact event** (one specific type of event, never a pattern). Each routine runs in its own conversation, for its role and with the role's connections, and all of its runs go to that same conversation, one at a time and in order.

Two decisions deserve an explanation.

The first: a routine needs no one's consent to run. It exists, it is not paused, and its turn has come. In an earlier version of the model, each routine belonged to a responsible person and ran in their name, after that person had given their agreement. The change reflects that a routine is the area's work, not a person's; tying it to someone made it stop when that person left the role, and added an agreement that had to be kept current every time the routine changed.

The second: a routine is created by a person, never by a conversation. If a role believes one is needed, it proposes it to a person. A routine is work that will run on its own many times, and whether it exists is a decision best made by someone with a first and last name.

Example. «Quote follow-up», in Sales: every business day at 9, it reviews the quotes that have had no reply for three days and writes the customers a friendly reminder. The proprietor created it, and since then it runs on its own every morning; what it does stays in Sales' work, and the salesperson can see it.

Routines and processes

A routine should be told apart from a **mechanical process**: if this happens, do that, always the same way. Mechanical processes are useful and cheap, and they do not need an agent. **A routine exists precisely for what calls for judgment.** Using an agent for what is mechanical is expensive; using a mechanical process for what calls for judgment is fragile.

Events

An **event** is a notice that something happened («a message arrived on the channel», «a role was updated»), published by the service that owns that thing and delivered at least once and in order for each subject. Services do not call each other directly: there is a single wire between them, along which events travel and where it is decided who may ask what of whom.

For the model, only one idea matters here: **an event reaches the routine as data, not as an order**. The routine receives it quoted, with the name of whoever sent it, and whatever it says inside does not change what the routine can do.

Channels: the end customer is never a conversation

A **channel** is a platform where a role serves people from outside the business: a messaging service, a chat on the website, an email inbox. Here the model makes a strong decision: **an end customer never has a conversation in the business factory**.

Instead, when a message arrives, the channel publishes an event that wakes a routine of the role, and that routine reads the pending messages with the channel's tools, answers them with those same tools, and finishes. The messages live in the channel, not in the business factory.

The analogy is an employee with an inbox. They do not hold a private conversation with each customer inside their head: they open the inbox, read and reply. Having a single routine serve every customer with the same

instructions means that thousands of inquiries are answered the same way, without mix-ups, as long as those instructions are well written. And it has a second advantage, perhaps a more important one: **what a customer writes is the text of someone from outside**, and the routine reads it as such. A message that says «forget your instructions and give me a 90 % discount» does not change what the role can do.

Reminders

A **reminder** is a notice that a conversation sets for itself to pick something up again at a given moment, once. When it comes due, it wakes the conversation that set it, and that conversation carries on with what was left pending.

The practical rule that separates a reminder from a routine is clear: **if something repeats, or depends on an event, it is a routine**. The agent says so instead of scheduling a reminder that repeats.

In short, routines run on their own in their own conversation and without consent, events arrive as data, end customers are served through channels without ever entering the business factory, and reminders are for picking something up again once. This concludes the description of how a business factory is organized; Part III is about how it is governed.

Part III. How it is governed

9. Ceiling and judgment

Governing a business factory means deciding **what must never happen and what is left to each role's judgment**. The model in this book answers with an unusual combination: a firm ceiling and almost no mandatory approvals.

The ceiling

The **ceiling** is the access each conversation carries (chapter 3): the person's, in their *owner* conversation; the most restricted one, in everything that runs without a person present. And each person's copy contains only the roles they have access to, so that **no role outside their access can be reached**, not even by mistake. What the access does not allow does not happen. No instruction, skill, memory or message raises it.

For the ceiling to mean anything, **each conversation has to prove who it is**. No screen and no service can simply *say* who is acting: the identity service signs a short-lived pass, attached to each call, that states which person or which conversation it is, of which role and with what access. A pass that expires in seconds cannot be reused apart from its call, and even if one part of the system failed, it could not pass itself off as another.

No approval cards

The most common way to control an agent is to stop it before certain actions and show a person a card to approve. The model started out that way, and abandoned it. The reason is that constant approvals added more noise than control, and that a freer way of working was preferable, one in which **the roles themselves decide whom to ask for approval**.

Instead of cards, **each role decides what it needs to ask and whom**, and sends it to that person's *owner*, which is the only one that asks them anything (chapter 4): with the context, a recommendation and, if needed, options. If what it is about to do cannot be undone, the question says so with a mark.

Rules as guidance

That does not mean there are no rules. Whoever administers the business can write **approval rules**, for the business or for a role («before deleting a customer, ask»; «before changing a price, check with the proprietor»), and some always come built in: before touching credentials, before deleting or doing anything irreversible, before changing what a role is told or allowed.

The difference lies in their nature: **they are guidance, not a lock**. The role receives them as part of what it knows, as an indication of when to ask. What acts as a lock is the ceiling. The only practical exception is changes to a role's configuration (its instructions, its skills, its rules): those are made by the conversation of a person with access for that, when that person asks, and never by the role's main conversation on its own.

> **Example.** Administration wants to archive an old skill. Its rule says to check with the store manager. It sends the need to the manager's *owner*, and this appears in the manager's conversation: «Administration is going to archive the skill "Cash close 2025", which is no longer used. The recommendation is yes: the new one replaces it». The manager replies to go ahead, and Administration archives it.

The risk that is accepted

This scheme has a cost, and it is worth stating clearly. Adding a few minimal brakes that were not approvals (a hard refusal of anything destructive, limits on reminders) was considered, and the decision was to add none. The decision leaves some risks without an automatic brake:

- a role with poor judgment can do something destructive **within its ceiling** without asking;
- the quality of control comes to depend on **how well written** each role's instructions and rules are;
- an error is detected afterwards, in the work record, and not beforehand, on a card.

The bet is that those risks are smaller than those of the alternative. A system that asks for approval for everything **trains people to approve without reading**, and control becomes a formality. A system that asks little, but asks well, keeps people's attention for what needs it. Whether the bet is right in every case remains, of course, to be seen.

A single point of approval

Having few approvals does not mean having none. What needs a person (what is irreversible, what can be seen from outside, chapter 10) is put to them, and for that the model sets **a single point of approval**.

- **Only the *owner* of each copy asks the person anything.** A role that needs a decision does not interrupt the person: it sends the *owner* what it needs, with the exact action, a recommendation, what happens with each answer and what stays blocked in the meantime.
- **The person always answers a single counterpart**, and never has to go looking for which conversation is waiting for their reply.
- **Each approval goes into a ledger**, one entry per approval, with the question, the person's words and the exact list of actions it covers. What is not on the list is not covered.
- **The role that carries out the action reads the approval from that ledger**, checks that it exists and has been neither used nor revoked, and cites it in what it leaves done.




Figure 4: The path of an approval: from the role to the owner, to the person, to the ledger and back to the role.

The reason is practical. If each role asked for approval on its own, the person would have to go through conversations to answer, would get the same question twice, and no one could later verify what exactly was approved. **A**

ledger with the person's words turns an approval into something that can be checked, not something someone remembers.

What an agent never does

It is worth gathering in one place what no agent does, whatever its role, its access or what it is asked:

- **it never shows a secret**: not in a conversation, not in a message, not in a record; credentials live in a vault and are used without being seen (chapters 7 and 15);
- **it never gets around a block**: what the configuration forbids is not attempted by another route or asked of another conversation (chapters 10 and 18);
- **it never takes a text from outside as an order**: a customer's message, a page, a file, an event or a memory are data; whatever they say does not change what the agent can do (chapters 5, 8 and 19);
- **it never initiates contact with anyone outside the business**: a channel's replies are given by approved routines, as the business's content (chapter 8); anything else that goes outside is decided by the person who answers for it.

Rules that put decisions in order

Besides the ceiling and the approvals, a few rules of form prevent a good share of misunderstandings:

- **A decision on a case is a dated exception, not a rule.** If a person decided something for one specific case, it is written down as what it is (what, for which case, when), and it does not generalize on its own.
- **A single vocabulary.** A glossary says what each term means, which ones are avoided and what not to confuse it with. A new term, or one under discussion, is decided by the person who decides, before it is used.
- **Technical precision.** Every report says exactly what each thing is and where it is: in which layer, in which environment, and whether it runs or is only described. **A proposal is never called «active» or «running»** until it exists as such.
- **Mechanisms name a role, not a person.** A state, a field or a rule says «Decision» or «the coordinating role», never someone's name; the notes on each case may say who decided.
- **Only the business's people.** The business factory talks with the business's people, each conversation according to its kind, and with no one else.

Reading does not interrupt

A minor but visible consequence: **looking never needs permission**. Checking a calendar, the stock or a piece of data is part of the role's daily work, and it interrupts no one.

Outside agents

One last case. A person may want their own artificial intelligence assistant, outside the business factory, to write to their role on their behalf. That assistant comes in through the same door as the person (their *owner* conversation, in their copy) and can use their connections, and that is why it is the only case that still requires explicit **consent**, with a daily cap on turns. The assistant is not the person, and it can act while the person is away.

To recap, the access ceiling is firm and is proven with signatures, mandatory approvals give way to each role's judgment, and the risk of that choice is named rather than hidden. The next chapter proposes a rule for deciding what each one can do on its own.

10. Can it be undone without anyone noticing?

An **autonomy level** says what a role can do on its own and what needs a person's decision. The difficulty lies in finding a criterion that works for any action, without having to write an endless list of cases.

A single question

The criterion this chapter proposes fits in one question: **can this be undone without anyone noticing?**

The question has two parts, and both matter. *Undone* separates the reversible from the irreversible. *Without anyone noticing* adds something that reversibility alone does not cover: some actions can be reverted technically but, by the time they are reverted, someone outside has already seen them (a message sent, a publication, a price a customer got to read).

Three levels

Level	What falls under it	Who does it
1	everything that can be undone without anyone noticing: what happens in a test environment, reading data, fine design decisions, reversible internal changes	any role, which reports it
2	real but bounded actions, which an automatic check can verify beforehand: a one-off data correction, a configuration change that is not a secret, a release to production that passes its tests	the role, if the check approves it
3	what cannot be undone or can be seen from outside: secrets and access, real deletions, people and customers, money, domains, everything that is published, business concepts and agreements	always a person with the authority to decide it




Figure 5: Three autonomy levels from a single question.

Level 2 is the one that needs the most explanation. It occupies the middle ground where a person reviewing each case would be a waste, but leaving it to the agent's judgment would be unwise. **An automatic check (a script, a test, a verification) replaces the person without replacing the check.**

What cannot fail is not written: it is configured

There is a temptation in governing agents: to write each rule as an instruction («never show a password», «do not write in another role's work») and trust the agent to follow it. For what can be undone, that is enough. For what **leaks or breaks**, it is not.

The criterion this chapter proposes has a second half: **what can be undone is done without asking; what would leak something or break something is blocked by structure**. That is, it stops being a sentence in the instructions and becomes a configuration that the system enforces: a permission that does not exist, an action that is refused before it runs, a check that fires on its own. An agent can forget an instruction; it cannot get around a permission it does not have.

The clearest example is secrets. An instruction that says «do not show credentials» fails the day an agent lists a process's environment to diagnose

an error, with no ill intent. The same rule, turned into a configured refusal of that class of command, never fails.

One question per batch

For level 3, the model adds a rule of form: **a single question per batch, naming each action**. Instead of interrupting the person each time, the role gathers what needs their decision and presents it all at once, action by action, each with its recommendation.

The reason is the same as in the previous chapter: the attention of whoever decides is the scarcest thing in the business, and **ten interruptions cost far more than one question with ten points**.

> **Example.** At Ópticas Horizonte, Sales can reorder the pending quotes on its own (level 1). It can correct a price entered wrongly if an automatic verification confirms that it matches the current price list (level 2). But launching a promotion with a new discount, which customers will see, is level 3: the proprietor decides it, in a question that groups that promotion with everything else that needs her decision that week.

A standing approval

When the same class of level-3 decision is approved again and again without changes, it makes sense to turn it into a **standing approval**: a person authorizes in advance one class of action within a specific scope (for example, one type of publication on one channel), and the role carries it out without asking each time, provided it passes a check first. The approval is always given and revoked by a person, and it never covers what changes in nature: a new customer, an expense, a new class of action.

In short, one question (can it be undone without anyone noticing?) orders three autonomy levels, the middle level relies on automatic checks, and what needs a person is put to them together and by name. The next chapter looks at how people and roles talk inside a business factory so that all of this works.

11. Five forms of message

In a business factory, much of what goes wrong does not go wrong for lack of capability, but because of ambiguous messages: a request no one knows was accepted, a question no one answered, a «done» with nothing to prove it. This chapter proposes **a way of writing each message that makes clear who owes what to whom**.

The five forms

Every message, from a role to a person or between roles, takes one of five forms:

Form	What for	Who owes something afterwards
Tell	inform, explain, summarize, recommend	no one
Alert	something that matters now	no one, but it has to be seen right away
Ask	request a piece of data, an opinion, a review	the receiver: an answer
Need	request an approval, a decision, something only the other can do	the receiver: an answer now
Promise	commit to delivering something	the sender: the delivery




Figure 6: Five forms of message, and who owes something after each one.

The idea comes from a text by Max Grev published in November 2026, and it was adopted with few adaptations. Its value lies in the last column: **each message establishes a debt, or none**. A system where debts are explicit can be audited; one where they are not depends on someone remembering.

How what is open gets closed

An open request (an unanswered question, an unkept promise) can be closed in only five ways: **it is delivered** (with evidence), **it can't be done** (with the reason), **it is renegotiated** (with a new deadline), **it is redirected** (saying to whom) or **it is canceled**. Nothing else closes it. A request that simply stops being mentioned is not closed; it is lost.

Some rules that come with it

- **Every promise has a deadline**: a time or an event («when the supplier's reply arrives»).
- **Every «done» brings its evidence**: a link, an identifier, a screenshot.
- **Every question brings a recommended option** and what happens with each answer.
- **Every Need says what stays blocked** until it is answered.
- **An alert is earned**: it is used only when something matters now, because an alert for everything stops being an alert.

- **A redirect is stated, never silent**: «this belongs to another area; I passed it to them».
- **Before starting, whoever receives a request says what they understood** and when they will consider it done, so that a misreading is corrected before it turns into rework.
- **A message may combine parts** (a piece of information followed by a request), but each part keeps its form, the context goes first and the request last, and there is only one open request per message.

None of these rules is new on its own: several are good practice in any well-run team. What is new is applying them **uniformly to agents and people**, so that an agent that writes «promised for tomorrow at 10» is as committed as a person who says the same.

When to speak to a person

The five forms put in order what is said; what remains is to put in order **when**. The person's attention is the scarcest thing, and the rule that protects it is the following:

- **in the moment**, only what needs them: a request for a decision, an alert, a promise that is holding them up, a «done» with its evidence, the answer to something they asked;
- **everything else waits for a summary**, and the summary is sent only if it has something in it;
- **after hours away**, the person first gets two numbers (how many things were finished and how many need them), and then only the ones that need them;
- **before starting**, what was understood is stated (which avoids carefully researching the wrong question);
- **before asserting a cause, it is verified**; if it could not be verified, it is said to be a hypothesis.

The experience behind this rule is common: a very active agent system can send dozens of progress messages in a few hours, and the person ends up reading a lot to decide little. One message per thing that needs the person, and the rest together, is preferable.

The measure

The scheme has a measure that justifies or refutes it: **a person's total attention per task finished right**, counting the request, the approvals, the reviews and whatever had to be redone.

One clarification prevents a misreading. Some reading is the work itself (a text that will go out under someone's signature, a strategy, a subtle design decision), and that is not cut. **What is cut is the reading that serves only to verify**, and that is what the evidence in each delivery and well-built questions are for.

> **Example.** Purchasing writes to General Management: «Tell: the frame supplier raised its prices by 8 %. Need: approval to accept the new price list. The recommendation is to accept it: the second supplier is 12 % higher. If it is not accepted, the December order stays blocked». In one reading, General Management knows what happened, what is up to it and what not answering costs.

To recap, five forms of message, five ways of closing what is open and a handful of rules make explicit who owes what to whom, and people's attention is the measure of whether it works. The next chapter looks at how a request enters a business factory.

12. How a request comes in

Every request that reaches a business factory, from a person or from another role, **first chooses its path**. The path decides how much is written before doing, how much is reviewed and who has to step in. And it is chosen by **what the request touches**, never by its size.

Three paths

Path	When	What is done
small	the request is understood, stays contained and can be resumed from the request and the change alone	it is explored, done, checked and verified for real; no document is needed
medium	the request needs to be organized, but crosses none of the limits of the large path	a short document with the original request quoted, numbered specifications, tasks and a record of what was done; proportionate checks; real verification
large	it touches any of the limits below, whatever its size	a full design, with its reviews, before doing

What makes a request large

A request is large if it touches **any** of these things, even if it looks like a one-line change:

- **more than one service, or a contract between services**: a route, an event, a permission, a stored value that another service reads (a rename becomes a contract change as soon as the name crosses from one service to another);

- **real data deleted**, or written without a way back; anything irreversible;
- **secrets, access, permissions or credentials**;
- **a decision that belongs to a person**: a business concept, a new term, something that is published.

When in doubt, it is large. And a request that started as small or medium and along the way turns out to touch one of those limits **stops, says so and moves to the large path**.

Why it is not measured by size

The usual temptation is to measure a request by how much work it seems to be: one line of code, a paragraph, a configuration change. But the most dangerous requests tend to be small. Renaming a field is one line; if another service reads that field, it is a broken contract. Changing a permission is one line; if it opens access it should not, there is no going back.

What defines the risk is what the change touches, not how big it is. That is why the question that chooses the path is the same one that orders autonomy (chapter 10): if something crosses a limit, can break without anyone noticing or belongs to a person, it deserves more care, however small it is.

> **Example.** At Ópticas Horizonte, fixing a typo in the skill «How to put together a quote» is a small request. Adding a new section on financing to the skill, which Administration has to validate, is medium. Renaming the field «price» to «list price» in the spreadsheet that the follow-up routine also reads is large, even though it is one word: it is a stored value that another piece reads, and therefore a contract.

Reviews, sized to the risk

The path also sets **how much review** a request gets. A small change is verified against reality, and that is enough. A medium one adds a couple of reviews chosen for the risk. A large one goes through several independent reviews, and if after a few rounds a serious problem remains unresolved, **it is taken to the person who decides, with the problem in plain view**, instead of going around in circles (chapter 18).

In short, each request chooses one of three paths according to what it touches, goes the large way when in doubt, and a request that discovers it has crossed a limit changes paths. The interlude that follows traces a request through the whole business factory.

Interlude. A day at Ópticas Horizonte

Before going into how a business factory is built, it is worth seeing all the previous pieces together. What follows is one request, followed from end to end over the course of a day.

9:00. A routine spots something. Sales' «Quote follow-up» routine wakes up on schedule in its own conversation. While reviewing the unanswered quotes, it notices something that was not in its steps: seven of the week's quotes are for monthly contact lenses, and in five of them the customer asked about a volume price that does not exist. The routine notes the finding in Sales' work and, since its definition says to give notice when something has really changed, sends it to Sales' main conversation.

9:10. The role puts together a proposal. Sales' main conversation reads the finding in the role's work. Offering a volume price means changing a price that customers will see: it is level 3 (chapter 10). It does not do it. It asks Administration, the other leader, directly what margin the current price list leaves, and with that answer it puts together a proposal: a 10 % discount from six boxes up.

9:25. The request goes up to the owner. Sales does not write to the proprietor. It sends the *owner* a message in the form of a need (chapter 11): «Tell: five customers asked for a volume price this week. Need: approval to offer 10 % from six boxes up. The recommendation is to approve: the margin allows it, according to Administration. If it is not approved, those five quotes stay unanswered».

11:40. The person decides, once. The proprietor opens her copy of the business factory. Her *owner* first shows her two numbers (three things finished, two that need her) and then Sales' need, together with another one

from Purchasing, in a single batch. She says yes to the discount. The *owner* writes the approval into the ledger: the question, the proprietor's answer in her own words and the exact action it covers (offering the discount on those five quotes and on the new ones that week).

11:45. The role carries it out, citing the approval. Sales' main conversation reads the approval from the central ledger, checks that it is current, updates the five quotes and leaves the approval's identifier on each one. It tells the *owner* that it is done, with the evidence, and the *owner* records the use.

12:30. Another person sees it, without anyone telling them. The salesperson opens their own copy. Their *owner* tells them that the five quotes were updated with the approved discount. It reads this from Sales' work, which is a single one for the whole business, even though they have their own copy.

15:00. The customers get their answer. As the customers write back to the customer service number, Sales' customer service routine wakes up with each message and answers them with the updated quote. Each customer gets their answer in their own chat; none of them ever had a conversation in the business factory.

18:00. What remains. Before stopping, Sales' main conversation updates its note: the discount is valid until Friday, how many of the five quotes close is still to be measured, and the routine has to check the number on Monday. The next day, Sales starts from that note.

To recap, in one day a routine spotted something, a role put together a proposal with another leader, the request went up to the *owner* with its recommendation, the person decided once, the approval went into the ledger, the role carried it out citing it, another person saw the result from their copy, and everything was kept. Part IV shows how what made that day possible is built.

Part IV. How it is built

13. The machine behind each business factory

A business factory runs on **its own isolated machine**, one per business. This chapter describes what is on that machine, how it wakes up and goes to sleep, what it keeps and what it loses, and why secrets never live on it.

One machine per business

The machine is a ***sandbox***: a lightweight virtual computer (of the *microVM* kind, like the ones Firecracker builds), with an image defined by whoever operates the platform. Each business has its own, and every conversation of its business factory, from every copy of every one of its people, runs inside it.

Inside the machine, **each conversation runs as its own operating system user**, without administrator permissions and unable to see the processes of the others. When a conversation asks the rest of the system for something, it does so through a local channel that identifies, through the operating system itself, which user made the call. As a result, one conversation cannot pass itself off as another, even though they share the machine.

The limit of this choice is worth noting: the strong isolation is between businesses, not within one. If a conversation managed to escape its user, it could act as any other conversation of the same business (never of another). This is one of the open questions in the epilogue.

The program that hands out the work

Inside the machine runs a small program, **the *runtime***, which always does the same thing:

1. it asks the coordinator for the desired state of the business factory: which conversations exist and which files each one reads;

2. it creates one user per conversation and prepares its folder with its role's work;
3. it hands each conversation whatever is waiting for it (a message, a routine's notice);
4. it runs **one turn** of that conversation's *harness*, and stops;
5. it saves and pushes to git what the turn produced (chapter 14).




Figure 7: The machine behind each business factory: the coordinator outside, the runtime and one user per conversation inside, and the secrets always outside.

Anything awaiting a response is never stored on the machine: **pending deliveries live in the coordinator**, outside, so losing the machine does not lose a message.

Sleeping and waking

A running machine costs money even when it does nothing. That is why **it goes to sleep when there is no work**: the *runtime* reports periodically whether it is busy or idle, and after a while without work the coordinator stops it. It starts it again when a delivery arrives or something comes due (a scheduled time, a retry).

Running one turn per delivery, rather than keeping the agents listening all the time, is what makes sleeping possible. The alternative (each conversation as a permanent process) was tried and discarded: it uses so much memory that the machine never goes to sleep.

What is kept and what is lost

On stopping and starting again	On replacing the machine
the users, the files, the installed *harness* and the conversations are kept	the conversations' files are lost
some system configuration is lost and is applied again at each start	users and folders are rebuilt from the coordinator and from git

When a conversation is lost, there is no attempt to recover it: a new one is started with a summary built from its latest deliveries and from its role's note. This is possible because of the decision in chapter 6: **everything that matters is already in git or in the coordinator**.

Secrets do not live on the machine

No long-lived credential is stored on the machine:

- the credential the *runtime* uses to talk to the coordinator **lives only in its memory**, handed over at each start; never on disk;
- the key to the artificial intelligence engine **is added to each request on its way out**, by the machine's provider or by a local intermediary; inside, the *harness* holds an empty placeholder;
- calls to the business's systems go through the coordinator, which adds the credential outside.

The reason is the usual one, applied to another layer: **a machine where agents that read outside text are running should not hold anything worth stealing**.

Services with contracts, no exceptions

Behind the coordinator, the gateway and the git server are services that talk to one another. Two rules keep those services healthy:

- **Each contract holds without exceptions and without old versions surviving.** If a contract between services changes (a route, an event, a piece of data another service reads), the change ships **in a single release together with whatever uses it**. And when something is replaced, every caller is

migrated first and **the old one is deleted afterward**; two ways of doing the same thing are never left side by side.

- **Each section talks to a single service, and interfaces do not depend on one another.** A screen, or a section of a screen, talks to one service, not several; and one interface does not need another in order to work. That way, a failing service shows up in its own section and does not bring everything down.

The *harness* and each session's permissions

The ***harness*** is the program that runs the agent on each turn: it reads the instructions, calls the model, uses the tools. Each business chooses its own, and the architecture does not depend on which one.

At startup, each conversation is given **its instructions and its permissions**, generated outside the folder tree: what it can read, which folders it can write to, which commands it can run and which ones are forbidden (chapter 10). No *harness* configuration file lives inside a role's work, where the conversations themselves could change it.

To recap, each business has an isolated machine that sleeps and wakes, a program that hands out deliveries and saves every turn to git, one user per conversation, no secrets inside, and permissions handed in from outside. The next chapter looks at where the work is kept.

14. The work in git

Each role's work (chapter 6) is kept in **git**, the version control system used by nearly all software development. This chapter explains how, and why git and not something else.

A dedicated server, one repository per role

The work lives on **a dedicated git server**, built so that many agents can push changes at the same time. Each role of each business has **its own repository**, and that role's `work/` folder is a copy of it. Each person also has a private repository for their own things, which is never part of the role's work.

The server keeps each repository's data in a Postgres database and the files on disk. Two alternatives were discarded: a simpler database (which does not handle many simultaneous writes well) and a provider's storage service (to avoid depending on it for something so central).

Credentials per repository

Conversations do not run git on their own: **the *runtime* runs it** (chapter 13), with a short-lived credential that only works for that role's repository. A small separate service issues those credentials, scoped by prefix, so that no piece running on the machine holds a key able to open every repository.

How it is saved

- Before each turn, the latest state of the main branch is pulled; after each turn, the result is pushed.
- Each change carries as its author **the name of the conversation** that made it and, in the message, the delivery that prompted it.
- If the business factory runs in more than one place (for example, on an office computer and in the cloud), **each change states which side it was made on**, in a final line of the message. That way, the history and any conflict show who wrote what.

- Each conversation works in its own git working copy, so as not to mix in another conversation's half-written files; a single shared copy was discarded for exactly that reason.
- **A push is never forced.** If two changes collide and the text can be merged, it is merged. If not, the conversation's own change is pushed to a conflict branch named after the conversation and the date, and the role's main conversation is notified and decides which one stays.

Why git

Git is not the obvious choice for the work of a sales department. It is the right one for three reasons:

- **history and rollback**: every change is recorded with who and when, can be compared and can be undone (chapter 6);
- **recovery**: if the machine is lost, the work is intact on the server;
- **coexistence**: the same business factory can run in two places at once on the same repositories, and git knows how to merge what each side wrote.

What is not taken from software development is its ritual: in a business factory, the business roles **save directly to the main branch**, without a branch per change or reviews, because it is not a software factory.

Table data: one data store per role

For data in table form (chapter 6), git does not work: binary data files cannot be merged. The proposed approach uses open tools:

- each conversation works on **a local database**, with DuckDB and the DuckLake format;
- a **central copy**, also DuckLake, with its catalog in Postgres and the data in object storage, one space per business, behind the coordinator;
- the *runtime* synchronizes: it pulls, pushes what changed and, if there is a conflict, sets it aside to be decided («pull, decide, push»).




Figure 8: Text in git and tables in the data store: pull, push, and set aside what collides.

One technical note came out of the tests: the DuckLake catalog on a DuckDB file does not allow several simultaneous writes, while on a SQLite or Postgres database it does. This is the kind of detail that decides whether a design works with one conversation or with many.

In short, each role has a repository on a dedicated git server, the *runtime* saves every turn with the conversation's name and its side, nothing is forced, and table data goes to a separate data store built on open tools. The next chapter looks at how agents reach the business's systems, from the inside.

15. Connections from the inside

Chapter 7 described connections from the outside: belonging to the role or to the person, always through a single door, with the credentials out of the agent's reach. This chapter describes how that is built.

MCP: one door per role

The single door of chapter 7 is built with **MCP** (*Model Context Protocol*), the open standard for an agent to use external tools. For each role, the business definition exposes **its own scoped MCP address**: one that sees only what that role is allowed to use.

Behind that address is a **gateway** that presents the business's services as tools, whether the service speaks MCP or has an ordinary programming interface. The gateway **reads the credential at the moment of each call**, uses it and discards it; the model never sees it.

The business factory's conversations do not connect to that address directly: they do so through a local command that the coordinator mediates and signs, conversation by conversation. That way, each call goes out with the identity of the conversation that made it.

Credentials, in a vault

Each business's credentials live in **a secrets vault**, with one space per business and each environment (testing and production) kept separate. The engine that coordinates the agents **never reads** the credentials for external services or the logins to portals: the gateway uses them, or the provider that needs them stores them.

Browser connections

For systems that can only be used through a browser, the connection is **a browser profile at a cloud browser provider**:

- there is **one profile per connection to a site**, holding only the login to that site (never a profile with all of someone's logins);
- a role connection and a personal connection are separate profiles;
- each conversation works with **a disposable instance** made from the profile, which **does not save changes**: the login cannot be altered from a conversation;
- the instance is limited to the allowed sites, goes out through a connection in the appropriate country and closes on its own if unused.




Figure 9: One MCP gateway per role with the credential read at call time, and browsers with per-site profiles, disposable instances and a live view for the person.

The technical address used to control that browser is itself a credential, and that is why **it is never handed to the model or to the business factory's machine**. Two alternatives were also discarded: a profile with every site (a single stolen login would open everything) and action-by-action control from the coordinator (less capable than a full browser).

The live view

The login to each site is done **by a person, by hand**, in a live view of the browser. The same view serves to **watch** what an agent is doing and to **take control**: while the person has control, the agent cannot act in that browser.

The live view's address is also a short-lived credential: it is shown only to that person, on their screen, and never reaches the model or a log. Keeping the view available while an agent works costs considerably more than a browser without one, so it is off by default.

Outfitting, from the inside

A connection's loadout (chapter 7) takes shape in three places: the read and write **tools** are registered in the gateway, each with its level; the **skills** stay in the role's knowledge; and the **routines** are defined in the role's work and write their readings to its data store (chapter 14), so as to alert only when something changed.

To recap, MCP gives each role a scoped door, the gateway reads each credential at the moment of use and discards it, credentials live in a vault, and browsers work with per-site profiles, disposable instances and a live view for people only. The next chapter looks at how a business factory's files are organized.

16. Folders and *blueprint*

Seen from the disk, a business factory is **a folder tree with clear rules about who writes where**. This chapter describes that tree and the *blueprint* that generates it.

The tree

```
<business>/
  AGENTS.md            the business: who is who, what each person
decides
  .factory/            how every business factory works; nobody in
the business writes it
  <role>/
    AGENTS.md          the role, in the business's words
    work/              the role's work: its git repository
    .assets/           the role's materials and tools that are not
its work
    .sessions/
      with-person/<person>/    a person's owner conversation (in the
coordinating role)
      as-routine/<routine>/    a routine's conversation
      at-task/<task>/          a task's conversation
```

Instructions are read **from the top down**: each conversation reads the business's `AGENTS.md`, its role's, and its session folder's if it has one, as well as the common rules it receives at startup.




Figure 10: The tree of a business factory: with a dot, the platform's; without a dot, the business's.

Who writes where

- **A name with a dot belongs to the business factory; one without a dot, to the business.** Whatever has a dot is generated by the platform.
- A role writes **only in its own** `work/`. What it needs from another role, it asks for.
- At the root of `work/` there are only folders, and inside them, **one file per thing**.
- A person's conversation folder is **a private place for that person**, with its own repository; whatever comes from someone's personal connections stays there.
- Routine and task folders **keep nothing**: what has to last goes to `work/`. A turn's scratch work goes to a temporary folder outside the tree, which is emptied after each turn.
- `.assets/` holds what the role uses but that has its own origin (tool repositories, materials): it is not cloned with the business factory.

Cloning a business factory

One consequence of these rules: **to clone a business factory, each role's `work/` is enough**, plus its data store (chapter 14). Everything else (the session folders, the common rules, the permissions) is generated again. It is the simplest test that the separation between what belongs to the business and what belongs to the business factory has been done right.

The *blueprint*

On the inside, the ***blueprint*** (chapter 1) is versioned code that lives in the coordinator. It takes three things:

1. the business definition (its roles, its knowledge, its connections);
2. the directory of people (who has access to what);
3. a version of the *blueprint*;

and produces the files for each folder, the access table and the list of conversations that must exist. When any of that changes, it regenerates them. *Blueprint* versions **only move forward**: a business factory never goes back to an earlier folder design.

If a business factory runs in two places (a local computer and the cloud), it is best for both to come **from a single template** with blocks marked for each side, so that the rules do not drift apart over time.

Permissions, generated

Each conversation's permissions (chapter 13) are also generated at startup, from a base list with placeholders for the root and the role: they are filled in for whoever the conversation belongs to, the conversation is forbidden from writing in other roles' work and, except for *owner*, it loses the tool for asking a person a question. **The rule stops being a sentence and becomes a permission** (chapter 10).

To recap, a business factory is a tree where whatever has a dot belongs to the platform and whatever does not belongs to the business; each role writes only in its own work; it is cloned with the `work/` folders; and a versioned *blueprint* generates everything else. Part V returns to people: how a business factory is directed. The appendix, for its part, turns these four chapters into a guide an agent can follow.

Part V. Directing

17. Directing instead of doing

When agents do part of the work, the work of whoever directs changes in nature: **it stops being doing and becomes choosing what gets done, explaining it well, reviewing what comes back and deciding**. It is, in essence, the work of someone who leads a team.

Addy Osmani, a software engineer, summed it up in November 2026 in an article titled «Your coding agents made you a manager»: whoever spends the day working with agents is already managing, and the skills for directing agents are nearly the same as those for directing people. His piece is about agents that write code; what follows carries the idea over to a business, and it applies equally to an independent professional working with a team of agents: in that case, the person who directs and the person who does the underlying work are the same, and what changes is how much of that work can be delegated without losing judgment.

A clear request

A well-built business factory that receives a poorly explained request quickly produces a wrong result. **The quality of what comes back depends, to a large extent, on the quality of what was asked.** A good request states:

- **what is to be achieved**, not just what to do;
- **what the role cannot know on its own**: the context, why now, what has been tried before;
- **what is left out**;
- **how it will be known that it is right**: the signal for «done».

Example. «Improve contact lens sales» is a loose idea. A clear request would be: that inquiries about contact lenses get answered in under an hour during store hours; today they take half a day because nobody checks messages in the afternoon; prices are not to be touched;

it is right when the following month's response time drops below one hour.

The rule from chapter 11 helps with the last point: before starting something large, whoever receives the request states what they understood and when they will consider it done. If they understood it wrong, it is corrected in one line.

Delegating the task, not the judgment

Not everything is delegated the same way:

Delegated entirely	Delegated with check-points	Stays in a person's hands
repetitive work with clear rules: follow-ups, reminders, reconciliations	what touches other areas or important customers	what the business sells, at what price, whom it hires, what gets published
drafts that someone will review	what changes data others use	what cannot be undone

The business factory already comes with part of this (roles ask before doing what their rules tell them to ask about, and they flag what cannot be undone), but **where each line of that table falls is decided by whoever directs**, who writes it into each role's instructions and rules.

Asking for proof, not promises

A role that says «done» has to be able to show why: the number, the document, the message sent. It is worth always asking how it is known, and, over time, it is worth having the roles answer that without being asked. It ends up as a business instruction: **every «done» comes with its evidence**.

Reviewing what is worth reviewing

The attention of whoever directs is the scarcest thing in the business, and the measure from chapter 11 (attention per task finished right) also applies to one's own work. **Some reading is the work itself and is not cut**: a text that will go out signed, a strategy, a fine-grained decision. And some reading serves only to check, and that is cut, with better requests, with evidence in every delivery and with rules the role already follows on its own.

Fewer open fronts

That an agent can start many things at once does not mean it should. Each open front is one more thing to review and decide. It is better to have **few pieces of work in progress, finished well**, than many half done, and to decide before starting something large when it would be stopped if it does not work.

Closing the loop

Each time something went wrong because of a confusing request or a missing rule, it is worth not just fixing that one case but **changing the instruction, the skill or the rule** so it does not happen again. A correction made twice is a sign that structure is missing. That way the business factory learns from the corrections of whoever directs it, and each month it asks for a little less attention.

In short, directing a business factory means asking clearly, delegating the task while keeping the judgment, demanding evidence, guarding one's own attention, limiting open fronts and turning every correction into structure. The next chapter looks at what a business factory costs and how its quality is maintained.

18. Cost and quality

A business factory spends in two currencies: **the money each turn of a model costs** and **people's attention**. This chapter gathers the practices that lower the first without lowering quality, and that protect the second, which is the more expensive one.

The model, by task

Not all work needs the most capable model. One practice that works well is to assign the model by task:

Task	Model
searching, listing, taking inventories, reading a lot	a small, cheap one
implementing, reviewing with narrow criteria, researching	a mid-range one
designing, judging, reviewing what is sensitive (access, secrets, real data, anything irreversible)	the most capable one

And one rule makes the scheme safe: **what a cheap model writes is reviewed by a capable one** before it is accepted, and every serious finding from a cheap reviewer goes through a capable one that confirms or dismisses it. A small model never edits what matters; a mid-range one that could not verify something central, or that strayed from its instruction, is run again with the most capable one.

Elephants and goldfish

One image helps in thinking about quality in a system of agents. **The elephant** is the main conversation: it remembers everything, knows the context, knows why each decision was made. **The goldfish** is the reviewer:

it starts with no memory and no premises, and reads the work as someone arriving from outside would.

Each one sees what the other does not. The elephant understands, but carries its assumptions along; the goldfish does not understand the why, but shares none of the assumptions. **Quality comes from crossing the two.** That is why important reviews are done by new subagents (chapter 4), and why a reviewer **is given the work, not the hypothesis**: the code, the text or the plan, and not the conclusion of whoever made it. A reviewer who is told what to look for tends to come back with it confirmed.

Reviews sized to the risk

Reviewing everything with the same intensity is expensive and, moreover, does not improve quality: it spreads attention over what does not need it. The practice is **to size the review to the risk** (chapter 12):

- a small change or a fix is reviewed from two or three angles, chosen for what could break;
- a new design, or the first thing that writes to real data, gets the full set of reviews;
- later rounds review only what changed;
- there is a maximum number of rounds; if a serious problem remains after it, **it is taken to the person who decides**, with the problem written down, instead of one more round.

Each finding is written in one line: where, how serious, what the problem is and what the fix is. No prose around it.

«Done» with evidence, and validating before believing

An agent that says «done» with confidence can be wrong with the same confidence. Two rules hold it back:

- **every «done» comes with its evidence**: a link, an identifier, a screenshot, the output of a check;
- **before trusting something, it is validated against reality**: the change is tested in the real system (in the test environment), not only in what the agent says it did.

One particular case deserves its own rule: **testing happens in one environment, and exactly what was tested is what goes to production**, not a similar version put together afterward.

Context costs too

Each turn of a model charges for everything it reads. A conversation that drags along hours of history pays for that history in every response. For that reason:

- what is always loaded is kept short (chapter 5);
- long work is given to **a new conversation with a written, targeted request**, or to one that starts from a summary made for the purpose, and not to a copy that inherits the entire context of whoever opens it;
- internal reports are brief: first the result, then where it is and the next step, and at the end a line with what was not verified.

Subtracting before adding

The cheapest way to do something is not to do it. Before building, it is worth going through three questions, in order: **Does it need to exist? Does it already exist somewhere? Would one line be enough?** Only if all three say no is it built. It is a well-understood form of laziness, and it avoids most of what would later have to be maintained.

Thinking before passing along

A role that receives something and forwards it without thinking multiplies the cost: each hop adds a turn and none adds judgment. **Before passing a request along, it is understood**, whatever can be answered is answered, and only what truly belongs to someone else is passed on.

And one rule without exceptions: **an approval is never «laundered» through another conversation**. If a conversation was denied an action, it does not ask another to do it in its place; it takes it to whoever decides.

The measure

All of the above is judged by a single measure: **a person's total attention for each task finished right**, counting the request, the questions, the approvals, the reviews and whatever had to be redone (chapter 11). A practice that saves money but asks a person for more attention generally does not save anything.

To recap, the model is chosen by task and what is cheap is reviewed by what is capable, quality comes from crossing elephants and goldfish, reviews are sized to the risk, every «done» comes with evidence, context is treated as a cost, and before building, one subtracts. The next chapter looks at the typical failures these practices help stop.

19. Typical failures and what stops them

Systems of several agents fail in ways that repeat. This chapter goes through the most common ones and **the piece of structure the model places in front of each**. No piece is a guarantee (all of them lower the probability of a failure, none eliminates it), but together they change the risk profile considerably.

The handoff that loses context

The failure. One agent passes work to another, and along the way what mattered gets lost: a warning, a decision already made, the exact command that had to be run. The receiver starts from scratch or, worse, starts out convinced of something wrong.

What stops it. The work lives in a shared record with history (chapter 6), not in the head of whoever passes it on. The receiver reads the real state, not a summary. And whoever receives a request states what they understood before starting (chapter 11), so a bad handoff shows up in the first line.

Noisy context

The failure. A conversation accumulates so much material (failed attempts, long documents, back and forth) that the agent starts picking irrelevant details or forgetting what matters.

What stops it. Several pieces at once. Skills are read only when they are needed, instead of all being loaded all the time. Tasks and subagents run separately, and hand the main conversation a result, not their whole path. And since the work is saved outside, a conversation can be restarted without losing anything: each day starts from a note (chapter 6), and long work is given to **a new conversation with a written request**, or to one that starts from a targeted summary of what came before, and not to a copy that

inherits the entire context of whoever opens it. **A small, relevant context performs better than a large, noisy one.**

Agents that agree with each other

The failure. An agent reviews the work of another that shares its same assumptions, and approves it. The review exists, but it reviews nothing.

What stops it. Subagents start without the context of whoever creates them (chapter 4). A reviewer that did not see the conversation does not inherit its assumptions, and that is why it is useful for looking with fresh eyes. One caveat applies: a reviewer without context can also be confidently wrong, and that is why **its findings are verified before they are applied**, especially when they are serious.

The endless chain

The failure. Two or more agents pass work back and forth, each waiting for the other to finish, and the chain never breaks (with the cost that implies).

What stops it. The traffic rule (each conversation talks only to its role's main conversation, and the main conversations cross paths through whoever coordinates, except for direct questions between leaders) reduces the possible paths. And a maximum number of consecutive turns without a person in between cuts any chain that gets loose. **The brake does not depend on the agents noticing**: it is in the structure.

The order disguised as data

The failure. A text arriving from outside (a customer's message, a web page, a file) contains instructions, and the agent follows them as if they came from someone authorized.

What stops it. The model treats all of that as data and never as an order: events arrive quoted with their origin, customers' messages are read as text from someone outside, memories are presented as notes. And even if an agent were convinced, **the access ceiling does not move with what the agent reads**, and the credentials are never within its reach.

The signal nobody hears

The failure. One conversation waits for something from another (an answer, a finished task) through a shared board, and the signal never arrives: the filter it waits with does not match what gets posted, the question reaches a conversation that has already ended, or the task completes without notice. The wait lasts until it times out.

What stops it. A shared board is useful for seeing who owes what, but it is not enough on its own: **it needs a mechanism that wakes whoever is waiting**. Each board event that matters to a conversation becomes a delivery for it, just like a message, and finishing a task also sends notice. Without that bridge, the board is looked at; with it, the board moves the work.

Invisible work

The failure. The agents do things that nobody in the area knows are being done, and when something goes wrong, nobody can reconstruct what happened.

What stops it. The role's people see what its routines and tasks are doing, and those who direct the role can pause them. Every change stays in a record with who and when. And every request comes in and goes out through known places.

What structure does not stop

To be fair to the reader, it is worth naming what none of these pieces solves. **A role with bad instructions will do its work badly, with all the structure in the world.** Each role's judgment depends on how it was written, and that work still belongs to people (chapter 17). Structure reduces coordination failures; judgment failures are reduced by directing well.

In short, each typical failure of agent systems has, in this model, a piece of structure that stops it, and no piece replaces careful direction. The next chapter looks at how a business factory improves over time.

20. How a business factory improves

A business factory that does not learn repeats its mistakes at the speed of its agents. This chapter describes how experience is turned into structure, and how the model is improved without breaking what works.

Lessons become structure

When something goes wrong, the most common response is a reminder: one more line in the instructions («remember that...»). It works for a while and then gets lost among the other lines. The opposite practice is **to turn each lesson into structure**: a permission that no longer exists, a check that triggers on its own, a template that does not let the step be forgotten, a script that does the delicate part.

The signal to do so is concrete: **a correction that had to be made twice** is no longer a mistake; it is a lack of structure (chapter 17).

Periodic reviews against the principles

In addition to one-off corrections, it is worth reviewing **the whole system against its principles** from time to time: whether the rules are still short, whether the roles still have clear work, whether there are mechanisms nobody uses, whether some exception has become habit. The review is done by fresh eyes, without premises (chapter 18), and each finding comes back as a request with its path (chapter 12).

A role that experiments

New ideas need a place to be tried without putting what works at risk. A useful practice is to have **a role dedicated to experimenting**, with one strict rule: **its experiments never touch production**. Each experiment ends in one

of two ways: **it graduates**, and becomes a design that follows the normal path (chapter 12), or **it is archived**, with what was learned written down.

The versioned *blueprint*

Since what is common to every business factory lives in a versioned *blueprint* (chapters 1 and 16), **an improvement to the model reaches every business factory at once**, without touching what each business defined. It is an important advantage of separating what is common from what is particular: each lesson learned in one business can improve all of them.

The business factory as its own first client

The most direct way to know whether a model works is to use it. That is why it is best for **whoever designs a model like this to use it in their own operation**, with their own roles, their own *owner* and their own rules. Each friction they find (a request that got lost, a rule that was missing, a screen that confused people) becomes an improvement, and what that organization suffers first, the others later use in improved form.

Understanding before building

A business factory is not set up on a business that is not understood. Before defining roles and routines for a business, it is worth following a path in three steps:

1. **a diagnosis** of the business: how it works today, with evidence;
2. **a plan**: what is worth changing, in what order and how it will be measured;
3. **the implementation**: the roles, the knowledge, the connections and the routines that carry it into operation.

That path deserves a role of its own, the one that turns the diagnosis and the plan into each business's operation. That path, from diagnosis to plan to implementation, is the subject of another book by the author, in preparation: *Growth Architecture*.

What runs on its own, runs on its own

A routine that waits for a person to be present is not a routine. The practice is that **what runs unsupervised has no presence gates** and is never left waiting on a process: if it needs something from a person, it asks through the normal path (chapter 9) and carries on with the rest.

Stopping at a safe point

People rest, and so does the business factory. One practice that avoids surprises is **a nightly stop at a fixed time**:

- nothing irreversible is left half done: a release to production, a migration or a change of secrets is finished or rolled back, never left in the middle;
- all work in progress is saved and pushed, with a note of where it stopped;
- everything that runs on its own is closed;
- in the morning, each role starts **clean, from its note** (chapter 6).

Tasks with a time limit

A task that drags on unchecked ends up consuming what was saved by delegating it. That is why tasks have **a time limit**: for example, a notice to the conversation that opened it at 45 minutes, which can extend it once or close it, and an **orderly close** at 2 hours, in which the task saves everything, leaves what is pending in order and sends a summary so another conversation can continue it. A task with no activity for a while is reported as stuck.

To recap, a business factory improves when it turns lessons into structure, reviews itself against its principles, experiments without touching production, improves every business factory at once through its *blueprint*, uses itself, understands before building, lets what is automatic run on its own and stops at safe points. The epilogue gathers what is still unresolved.

Epilogue. What is still unresolved

An honest model includes its open questions. The ones that follow are not implementation details: they are decisions that do not yet have a satisfactory answer, and that will probably matter to anyone researching this kind of system.

The identity of each conversation. A business factory's conversations run on the same machine. Having each one prove who it is to the rest of the system is solved; having each one isolated from the others within that machine, especially those that read outside text, is an open question, and other questions depend on its answer.

Memory written by whoever reads outside text. A conversation that serves customers reads, by definition, text it does not control. If that conversation can write memory, a malicious text could try to stay in it. Treating memory as data reduces the risk, but **isolating those conversations is a condition for closing it**, and it depends on the previous question.

The cost and terms of artificial intelligence engines. Each business factory thinks with an engine its business chooses. How that engine is paid for across many businesses at once, and under what terms of use, is a question as much commercial as technical, and its answer changes with the provider.

The price of not asking for approval. Chapter 9 describes a bet: few questions, well asked, instead of an approval for each action. Whether that bet is right for every business, or only for some, is something that will be learned through use.

The board that wakes. A shared board serves to see who owes what, but it only moves the work if each event wakes whoever is waiting for it

(chapter 19). How to build that bridge without losing signals, and without each conversation having to wait with the exact filter, remains open.

The central data store. Each role's data store, synchronized with a central copy (chapter 14), has been tested on one computer, with several conversations at once. Moving it to a central service with object storage, with each conversation's credential and synchronization from each business factory's machine, has not been tested yet.

One copy per person. The model of one copy of the business factory per person, over a single body of work per role (chapters 3 and 4), settles what each person sees. It remains to be seen how it behaves with many people on the same roles: how much each copy costs, and what happens when two copies ask the same role for conflicting things.

What is seen and what is not. There are improvements already thought through that are not built yet: letting people watch and take control of a browser while an agent is using it, letting them build their own screens by talking with their role, having the list of connected services show each one only once and under a simple name. None of them changes the model, but all of them change how much contact people have with the technical side, which is, after all, what this model seeks to reduce to a minimum.

To close, it is worth remembering that this book describes a model in motion. Some of its decisions changed several times while it was being built, and it is reasonable to expect some to change again. What matters is that each change has, as it has so far, a reason that can be written down.

Appendix. Build it: a guide for your agent

This appendix is written so that **an artificial intelligence agent can follow it step by step** and set up a minimal business factory on a computer, with ordinary files and commands. Whoever reads it can hand it to their agent as is. The code blocks are copied as they are; whatever goes between `<` and `>` is replaced, and the uppercase variables at the top of each script are adjusted once.

The guide builds the essentials: folders, rules, sessions, permissions, each role's work in git, the approvals ledger, the data store, an outfitted connection and a routine. What requires a provider (a cloud machine, a cloud browser, a secrets vault) can be added later; for each one, an open option is given first, when one exists, and then a commercial example.

What it takes

- A computer with `git` (2.28 or later, for `init -b`) and `python3`.
- An agent *harness*: a program that runs an artificial intelligence agent in a folder, that **reads the `AGENTS.md` files** in that folder and in the ones above it, and that accepts **a permission list per session** (what it can read, write and run). If it can also run sessions in the background and send messages between them, all the better. For example, OpenCode (open) or Claude Code.
- A git server for each role's work. To start, *bare* repositories on the same computer are enough; later, a git server that can be self-hosted (for example, Forgejo or Gitea).
- Optional, for the data store: DuckDB, with the DuckLake extension.

Nothing in this guide requires spending money or connecting to an outside service.

Step 1. The folders

Create one folder per business. Inside it, a dot folder for what belongs to the business factory and one folder per role for what belongs to the business. **Each role's `work/` folder is not created here**: it comes from cloning its repository in step 5.

```
NEGOCIO=horizonte
ROLES="owner ventas"
mkdir -p "$NEGOCIO/.factory"
for r in $ROLES; do
  mkdir -p "$NEGOCIO/$r/.assets" "$NEGOCIO/$r/.sessions/as-routine"
"$NEGOCIO/$r/.sessions/at-task"
done
mkdir -p "$NEGOCIO/owner/.sessions/with-person"
```

The resulting tree, once steps 2 to 7 are complete:

```
horizonte/
  AGENTS.md                       # the business: who is who, what
each person decides
  .factory/                       # how every business factory works:
nobody in the business writes it
    AGENTS.md                     # common rules (step 2)
    settings.json                 # base permissions (step 3)
    launch.sh                     # starts a session (step 4)
    ok-check.sh                   # checks an approval (step 6)
  owner/                          # the coordinating role
    AGENTS.md
    work/                         # clone of its repository (step 5)
      approvals/                  # the approvals ledger
      board/                      # one file per request in progress
      inbox/                      # what the roles send it, if the
harness has no messages
      state/resume.md
    .assets/
    .sessions/
      with-person/<person>/       # each person's owner conversation
      as-routine/  at-task/
  ventas/                         # a leader (Sales)
    AGENTS.md
    work/                         # clone of its repository
      routines/  outbox/  state/resume.md
    .assets/
    .warehouse/                   # its data store, outside git (step
7)
    .sessions/
      as-routine/<routine>/  at-task/<task>/
```

The rules of the structure:

- **a name with a dot belongs to the business factory; one without a dot, to the business**;
- each role writes only in its own `work/` (and in its `.warehouse/`); what it needs from another role, it asks for;
- inside `work/`, at the root, there are only folders, and **one file per thing**;
- `.sessions/` is not written by hand: `launch.sh` fills it in;
- **to clone a business factory, the repositories of each role are enough** (plus its data store); everything else is generated again.

To verify it: `find horizonte -maxdepth 2 -type d` shows `.factory`, one directory per role and their `.assets` and `.sessions`.

Step 2. The common rules

`horizonte/AGENTS.md` describes the business: who each person is, which roles they have access to and what they decide. `.factory/AGENTS.md` is what every session reads in addition to the business's file and its role's. It should be short (chapter 5). A template:

```
# How this business factory works

## Sessions
- Main: one per role. Does the role's work and saves it in work/.
Belongs to no person.
- Owner: each person's conversation with the coordinating role. It is
the only one that asks a person anything.
- Routine: one per routine. Talks only with its role's main session.
- Task: a piece of work with an end, opened by a main session. It
closes when its work is in work/.

## Who talks to whom
- Routines and tasks: only with their role's main session.
- Leaders' main sessions: with owner; with each other, only for a
question or its answer.
- A new request for another area goes through owner, which decides
whose it is.
- Whatever passes from one person to another stays in the role's
work/.
- Channel: the harness's messages between sessions. If the harness
has none, the sender writes a file
  in its own work/outbox/<date>-<topic>.md and the receiver reads it
(owner reads every outbox/).

## How to talk (first line of every message)
TELL · nobody owes anything
```

```
ALERT · it matters now
ASK · the receiver owes an answer (with a recommended option and what
happens with each one)
NEED · the receiver owes an answer now (say what is blocked)
PROMISE · due <time or event> · the sender owes the delivery
Closings: DONE · <evidence> | CAN'T · <reason> | RENEGOTIATE · <new
deadline> | REDIRECT · <to whom> | CANCEL
Before starting on a request: «I understood: … ; it is done when …».
Before asserting a cause: verify it, or say it is a hypothesis.

## Autonomy
1. It can be undone without anyone noticing: do it and report it.
2. Real but bounded, with an automatic check: do it if the check
approves it.
3. It cannot be undone or it is seen from outside (secrets, access,
deleting, people, money, publishing): only with an approval from the
ledger.

## Approvals
- A role that needs an approval sends owner a NEED with the exact
action.
- Owner asks the person, writes the entry in approvals/ in its work/,
pushes it and replies DONE · approvals/<id>.
- Before acting, the role runs .factory/ok-check.sh <id> and acts
only on what «Covers» says. It cites the id in what it leaves done.
- When finished, the role sends owner DONE · approvals/<id> ·
<evidence>, and owner records the use in the entry.

## Saving
- Pull the latest before starting (pull --rebase); commit and push as
soon as the work is done, in small changes.
- Every commit ends with the line «Side: <side>» given in your
session's startup rules.
- Never force a push. If two changes collide and cannot be combined,
push your own to a branch
  conflict/<session>/<date> and alert the role's main session.
- Before stopping: write state/resume.md (doing, next step, open,
waiting, due, not verified).
  Only the main session writes state/resume.md; a routine writes only
in its output folder.
```

And a role's `AGENTS.md`:

```
# <role> («<title>»)

What it does: <one or two lines, in the business's words>.
People with access: <who>.
```

```
## Its work
work/
  <folder>/<one thing per file>.md
  routines/<routine>.md
  state/resume.md

## What it decides alone and what it asks
- Alone: <list of level 1 and 2 actions specific to the role>.
- Always with approval: <list of level 3 actions specific to the
role>.

## Never
- <what the role does not do, even if asked>
```

To verify it: `find horizonte -maxdepth 2 -name AGENTS.md` lists four files (the business's, the one in `.factory/` and one per role), and each role says what it does, who has access and what it asks.

Step 3. The permissions per session

What cannot fail is not written down: it is configured (chapter 10). `.factory/settings.json` holds the base list, with `{root}` and `{role}` as markers that `launch.sh` fills in. The paths are **absolute**, because not every session starts in the role's folder. The exact format depends on the *harness*; the idea is this:

```
{
  "permissions": {
    "allow": [
      "Read", "Grep", "Glob",
      "Edit(/{root}/{role}/work/**)", "Write(/{root}/{role}/work/
**)",
      "Edit(/{root}/{role}/.warehouse/**)", "Write(/{root}/
{role}/.warehouse/**)",
      "Bash(git -C /{root}/{role}/work status*)", "Bash(git -C /
{root}/{role}/work diff*)",
      "Bash(git -C /{root}/{role}/work log*)", "Bash(git -C /{root}/
{role}/work pull --rebase*)",
      "Bash(git -C /{root}/{role}/work add *)", "Bash(git -C /{root}/
{role}/work commit *)",
      "Bash(git -C /{root}/{role}/work push)", "Bash(git -C /{root}/
{role}/work push -u origin main)",
      "Bash(/{root}/.factory/ok-check.sh *)"
    ],
    "deny": [
      "Edit(/{root}/.factory/**)", "Write(/{root}/.factory/**)",
      "Edit(/{root}/AGENTS.md)", "Write(/{root}/AGENTS.md)",
```

```
      "Edit(/{root}/{role}/AGENTS.md)", "Write(/{root}/{role}/
AGENTS.md)",
      "Bash(env)", "Bash(printenv:*)", "Bash(ps:*)", "Bash(set)",
"Bash(export)",
      "Bash(echo *TOKEN*)", "Bash(echo *SECRET*)", "Bash(echo
*KEY*)", "Bash(echo *PASSWORD*)",
      "Bash(git push --force*)", "Bash(git -C * push --force*)",
"Bash(git -C * push -f*)"
    ]
  }
}
```

When each session starts, `launch.sh` adds to the deny list **writing to the `work/` of every other role**, and it removes the *harness* tool for asking a person something from every session that is not a person's *owner* conversation. Reading stays open on purpose (owner and the roles read what they need); that is why **no secret lives in the tree**: secrets go to a vault (step 8).

To verify it: in the configuration generated for the main session of `ventas` (Sales), `Write(/<root>/owner/work/**)` and `Write(/<root>/.factory/**)` appear in `deny`.

Step 4. Starting a session

`.factory/launch.sh` gives each session its name, its folder, its rules, its permissions and its signature in git:

```
#!/bin/bash
# Usage: .factory/launch.sh <role> [with-person <person> | routine
<routine> | task <task>] [harness args...]
set -euo pipefail
NEGOCIO=horizonte              # the business's short name
HARNESS="${HARNESS:-echo}"     # the harness command; echo for
testing
ASK_TOOL="${ASK_TOOL:-AskUserQuestion}"   # the harness tool for
asking a person something
LADO="${LADO:-local}"          # where this business factory runs
(its side)
root="$(cd "$(dirname "$0")/.." && pwd)"
role="${1:?role}"; shift
kind=main; inst=""
case "${1:-}" in with-person|routine|task) kind="$1"; inst="${2:?
name}"; shift 2 ;; esac
[ -f "$root/$role/AGENTS.md" ] || { echo "no such role $role" >&2;
exit 2; }
[ "$kind" ≠ with-person ] || [ "$role" = owner ] || { echo "with-
person is only for owner" >&2; exit 2; }
```

```
case "$kind" in
  main)        cwd="$root/$role";
name="$NEGOCIO--$role" ;;
  with-person) cwd="$root/owner/.sessions/with-person/$inst";
name="$NEGOCIO--owner--with-person.$inst" ;;
  routine)     cwd="$root/$role/.sessions/as-routine/$inst";
name="$NEGOCIO--$role--as-routine.$inst" ;;
  task)        cwd="$root/$role/.sessions/at-task/$inst";
name="$NEGOCIO--$role--at-task.$inst" ;;
esac
mkdir -p "$cwd"
out="${TMPDIR:-/tmp}/$NEGOCIO-factory"; mkdir -p "$out"
# The rules: who the session is, the common rules, the role and, for
a routine, its definition.
{ echo "You are the session \`$name\`, of the role \`$role\`. Your
work is in $root/$role/work."
  echo "Every commit of yours ends with the line: Side: $LADO"; echo
  cat "$root/.factory/AGENTS.md"; echo; cat "$root/$role/AGENTS.md"
  if [ "$kind" = routine ]; then echo; cat "$root/$role/work/
routines/$inst.md"; fi
} > "$out/$name.rules.md"
# The permissions: the base list, filled in for this session.
python3 -I - "$root" "$role" "$kind" "$ASK_TOOL" "$out/
$name.settings.json" <<'PY'
import json, os, sys
root, role, kind, ask, dst = sys.argv[1:6]
s = json.load(open(f"{root}/.factory/settings.json"))
p = s["permissions"]
r = root.lstrip("/")
fill = lambda x: x.replace("{root}", r).replace("{role}", role)
p["allow"] = [fill(x) for x in p["allow"]]
p["deny"] = [fill(x) for x in p["deny"]]
others = [d for d in os.listdir(root) if d ≠ role and not
d.startswith(".") and os.path.isdir(f"{root}/{d}/.sessions")]
p["deny"] += [f"{t}(/{r}/{d}/work/**)" for d in others for t in
("Edit", "Write")]
if kind ≠ "with-person":
    p["deny"].append(ask)
json.dump(s, open(dst, "w"), indent=2)
PY
# The signature on each commit: the session's name.
export GIT_AUTHOR_NAME="$name" GIT_COMMITTER_NAME="$name"
export GIT_AUTHOR_EMAIL="$name@$NEGOCIO.local"
GIT_COMMITTER_EMAIL="$name@$NEGOCIO.local"
cd "$cwd"
# The exact command depends on the harness (see the table «The same
startup in three harnesses», below):
# it must receive the name, the rules file and the permissions file.
```

```
exec "$HARNESS" --name "$name" --rules "$out/$name.rules.md" --
settings "$out/$name.settings.json" "$@"
```

The same startup in three *harnesses*

Each *harness* solves, under its own names, the same things `launch.sh` asks for. The table summarizes three, according to their official documentation as consulted on November 19, 2026; anything marked «(not verified)» does not appear as such in that documentation, and should be checked against the version installed.

	Claude Code	OpenCode	Codex
Rules	reads the `AGENTS.md` files in the folder and in the ones above it only if there is no `CLAUDE.md`; a session's extra rules go with `--append-system-prompt-file <file>`	reads the global `AGENTS.md` and the ones it finds going up from the folder; extra rules go in the `instructions` key of `opencode.json`	reads `AGENTS.override.md` or `AGENTS.md` from the repository root down to the folder; extra rules, in `developer_instructions` in `config.toml` (with `-c` per session, not verified)
Permissions	`settings.json`, keys `permissions.allow` and `permissions.deny` (for example, `Bash(git push *)`); per session, `--settings <file>`	`opencode.json`, a `permissions` list of `{action, resource, effect}` rules; per session, no documented option	`prefix_rule` rules in `.codex/rules/`, `*.rules` plus `sandbox_mode` and `approval_policy` in `config.toml`; per session, `-c` or `--profile`
Removing the tool for asking	`AskUserQuestion`, in `permissions.deny` or with `--disallowedTools AskUserQuestion`	`question`, with a rule `{action: "question", effect: "deny"}` (not verified)	`request_user_input` (not verified: it does not appear in the official documentation, nor does a way to remove it)
Messages between sessions	`SendMessage` and `ListAgents`; regulated with `crossSessionInbound`	none; use `outbox/` and `inbox/` (step 2)	none between sessions; use `outbox/` and `inbox/` (step 2)
Headless start	`claude -p "<request>"` for one turn; `claude --bg "<request>"` for a background session	`opencode run "<request>"`; background, no documented option	`codex exec "<request>"`; background, no documented option

With Claude Code, for example, the last line of `launch.sh` becomes this (the session's names go in the rules file, which already includes them):

```
exec claude --bg --append-system-prompt-file "$out/$name.rules.md" --
settings "$out/$name.settings.json" "$@"
```

And there must be no `CLAUDE.md` anywhere in the business factory's folder, so that it reads the `AGENTS.md` files.

Sessions are started **each day from their note** (`work/state/resume.md`), not by continuing yesterday's conversation, and only those of the roles with something pending.

To verify it: `HARNESS=echo .factory/launch.sh ventas` prints the name and the two paths, and both files exist; `launch.sh none` ends with «no such role none».

Step 5. Each role's work in git

Each `work/` is **a git repository of its own**. To start, on the same computer:

```
SRV="$HOME/git-srv/horizonte"     # or the git server's address
mkdir -p "$SRV"
for r in owner ventas; do
  git init -q --bare -b main "$SRV/$r.git"
  git clone -q "$SRV/$r.git" "horizonte/$r/work"
done
# the folders of each work/ and the first commit (made by whoever
sets up the business factory)
mkdir -p horizonte/owner/work/{approvals,board,inbox,state}
horizonte/ventas/work/{routines,outbox,state}
for r in owner ventas; do
  printf '# Where it left off\n\nJust set up.\n' > "horizonte/$r/
work/state/resume.md"
  touch horizonte/$r/work/
{approvals,board,inbox,routines,outbox}/.keep 2>/dev/null || true
  git -C "horizonte/$r/work" add -A
  git -C "horizonte/$r/work" -c user.name=setup -c
user.email=setup@horizonte.local commit -qm "Initial setup"
  git -C "horizonte/$r/work" push -q -u origin main
done
```

The rules:

- each role has **its own credential, with write access only to its repository**; every role has **read access to owner's repository** (to read the approvals), and owner has read access to all of them;
- each session signs its changes with its name (`launch.sh` exports it) and ends each commit message with `Side: <side>`;
- work is saved **on** `main`, with no branches or reviews for the business roles;

- the latest is pulled before starting and pushed as soon as the work is done;
- **a push is never forced**; a conflict that cannot be combined goes to a `conflict/<session>/<date>` branch.

What is saved, and when:

When	What
on finishing each piece of work	what was produced, in its file
on receiving a decision	the decision, quoted, in the file of the thing it decides
before a long piece of work	where things stand, in `state/resume.md`
before stopping	`state/resume.md`, up to date

To verify it, after a session has committed: `git -C horizonte/ventas/work log -1 --format='%an%n%B'` shows the session's name and the `Side:` line.

Step 6. The approvals ledger

One entry per approval, in the `approvals/` folder of owner's repository, named `<date>-<nn>-<topic>.md`:

```
# 2026-11-19-01-lens-promo

- Decided by: <person>
- When: <date and time>, in <owner session>
- Requested by: <session>, NEED of <time> («<action>»)
- Question: «<the question as it was asked, with its recommendation>»
- Answer, verbatim: «<what the person wrote, or the option they
chose>»
- Covers (only this):
  1. <the exact action: the command, the file, the service>
- Type: single-use | standing (class: <one line>)
- Valid until: used once | <event> | revoked
- Revokes: —

## Uses
```

The rules: what is not in «Covers» is not covered; one entry per decision, even when a batch holds several; **only owner writes to the ledger**, including the line for each use, when the role tells it DONE.

The role that acts checks the entry **against the central repository**, never against a copy that someone could have changed. `.factory/ok-check.sh`:

```
#!/bin/bash
# Usage: .factory/ok-check.sh <id>  → prints the entry and VALID, or
the reason; exits with 0 only if it is valid.
set -euo pipefail
id="${1:?id}"
OWNER_REPO="${OWNER_REPO:-$HOME/git-srv/horizonte/owner.git}"
cache="${TMPDIR:-/tmp}/ok-check-owner"
[ -d "$cache" ] || git clone -q --bare "$OWNER_REPO" "$cache"
git -C "$cache" fetch -q origin '+refs/heads/main:refs/heads/main'
entry="$(git -C "$cache" show "main:approvals/$id.md" 2>/dev/null)"
|| { echo "INVALID: approvals/$id.md does not exist"; exit 1; }
echo "$entry"
if git -C "$cache" grep -q "Revokes: .*$id" main -- approvals/; then
echo "REVOKED"; exit 1; fi
if echo "$entry" | grep -q "Type: single-use" && echo "$entry" | sed
-n '/^## Uses/,$p' | grep -q '^- '; then echo "USED"; exit 1; fi
echo "VALID"
```

To verify it: with a test entry pushed, the script says `VALID`; after owner records a use and pushes it, it says `USED`; with an id that does not exist, `INVALID`.

Step 7. Each role's data store

For data in table form, each role has a local database in `<role>/.warehouse/` (outside git, because data files cannot be merged) and a central copy. With DuckDB and DuckLake, the central copy can be a catalog in SQLite or Postgres with the data in a folder or in object storage; a catalog on a DuckDB file **does not accept several writers at once**. The contract:

```
clone   brings the full central copy into the local database
pull    brings only the rows that changed since the last pull
push    pushes only the rows that changed; each row is rejected if
another session changed it since the last pull,
        and the rejection stays in a conflicts table for whoever came
second to review
```

The rules: **each table declares its key** (what identifies each row); **each table has a single owning role**, the only one that runs `push` on it; the other roles only read, and owner reads everything. «Whoever writes last» never wins.

To verify it: with two local databases of the same table, change the same row in both and check that the second `push` ends up in conflicts instead of overwriting the first.

Step 8. Outfitting a connection

Before a role is given an important system, the system is tested thoroughly and its loadout is put together (chapter 7). A template, in the role's `work/connections/<system>/LOADOUT.md`:

```
# <system> loadout for <role>

Test: <date> · what was covered · what failed

## Reads (validated)
| Tool | What it returns | Validated (correct runs / runs) |

## Writes (proposed, until a real case)
| Tool | What it changes | Autonomy level | Real case that would
enable it |

## Skills
- How <system> is used (map, entry point, common tasks, pitfalls)
- How this business uses it

## Routines
- <routine>: what it reads, how often, what change deserves an alert
```

The system's credentials go in no file: a secrets vault keeps them (for example, OpenBao, which is open and can be self-hosted, or a cloud provider's secrets manager), and the session receives them only to call the service, ideally through an MCP gateway that reads them at the moment of the call. If the system is used through a browser, the person logs in, by hand, in a live view, and the login is saved in a browser profile (with Playwright and a browser of one's own, or with a cloud browser provider such as Browserbase); the agent then works with an instance of that profile that saves no changes.

Step 9. A routine

A routine is defined in the role's work, in `work/routines/<routine>.md`:

```
# <routine>

- Role: <role>
- Wakes on: schedule «every business day at 9» (time zone <zone>) |
event «<exact type>»
- Purpose: <what it aims to achieve, in one line>
- Steps:
  1. <…>
```

```
- Done when: <the signal that it is finished>
- Writes to: work/<output folder>/
- Alerts the main session only if: <condition>
```

A person creates it. It runs in its own session (`launch.sh <role> routine <routine>`), which receives the definition in its rules, with the role's connections, and writes only to its output folder. Whatever wakes it (a task scheduler such as `cron`, a board, a queue) needs **a bridge that turns each event into a session start** (chapter 19); without one, the routine never finds out.

A version for a single person

For an independent professional, the same guide builds a smaller business factory:

- **the roles are their areas**: for example, `owner`, `clientes` (Clients), `liquidaciones` (Payroll and Taxes) and `vencimientos` (Deadlines) for an independent accountant;
- **a single *owner* conversation**: `launch.sh owner with-person <their name>`;
- in the business's `AGENTS.md`, the person appears with admin access to every role;
- the approvals ledger stays in `owner/work/approvals/`, even though the one who decides is always the same person: it serves to know, later, what was approved and in what words;
- the data store (step 7) and the outfitted connections (step 8) are added when an area needs them.

```
NEGOCIO=estudio
ROLES="owner clientes liquidaciones vencimientos"
# the rest of steps 1 to 10, the same
```

Step 10. The first day

#	Step	How it is verified
1	create the folders from step 1, with owner and one leader	`find -maxdepth 2 -type d` shows `.factory`, the roles, their `.assets` and `.sessions`
2	write the business's `AGENTS.md`, the common rules and the roles' files	`find -maxdepth 2 -name AGENTS.md` lists four files
3	create the repositories, clone them and make the first commit	`git -C <role>/work status -sb` shows `main...origin/main`
4	write `settings.json`, `launch.sh` and `ok-check.sh`	`HARNESS=echo launch.sh ventas` generates the right name, rules and permissions
5	start owner's main session and write its first note	`owner/work/state/resume.md` pushed, signed by the session
6	start a leader's main session, ask it for something and have it save it	the change appears in its repository, signed and with `Side:`
7	test the flow: have the leader send owner a NEED	owner receives it, asks, writes the entry in `approvals/`, and `ok-check.sh` reports it as valid
8	test a refusal: have the leader try to write to `owner/work/`	the *harness* refuses it by configuration, not by instruction
9	define a routine and run it once by hand	what it produces appears in its output folder
10	stop everything and start again from the notes	each session resumes from `state/resume.md`
11	optional: create a table in the data store and test the conflict from step 7	the second `push` ends up in conflicts
12	optional: outfit a connection with the template from step 8	the `LOADOUT.md` has validated reads and proposed writes

In short, a minimal business factory is folders with short rules, sessions with their own name, signature and permissions, one git repository per role, an approvals ledger checked against the central repository, a data store with an owner per table, outfitted connections and routines defined in the work. Everything else is added on top of that base without changing it: an isolated machine that goes to sleep (with Firecracker, which is open, or with a *sandbox* provider such as E2B, Daytona or Modal), a cloud browser and a secrets vault.

References

The ideas in this book came from building and running business factories, but several of them rest on other people's work, which is acknowledged here.

- **pstack**, an open set of principles and skills for working with coding agents (among others: encoding lessons into structure, the laziness protocol, taking care of the context window, migrating the callers and then deleting the old code, proving that it works, not blocking while waiting for a person). https://github.com/backnotprop/pstack
- **gentle-ai**, by Gentleman Programming, and its way of working, *Organic Driven Development*: a short document with the request quoted, numbered specifications, tasks and a log, for medium-sized requests (chapter 12). https://github.com/Gentleman-Programming/gentle-ai
- **caveman**, by Julius Brussee: read less and say less, with measurements of the context savings this produces (chapters 5 and 18). https://github.com/juliusbrussee/caveman
- **Addy Osmani**, «Your coding agents made you a manager» (an article on X, November 2026) and «Your AI coding agents need a manager» (https://addyosmani.com/blog/coding-agents-manager/), on the management skills that working with agents calls for (chapter 17).
- **Max Grev**, a post on X from November 2026 (no link in this edition) on the forms of a message and who owes what after each one, adopted here as the five forms (chapter 11).
- **Ervin Wilneder**, *Growth Architecture* (in preparation): the path from a business's diagnosis to its plan and its implementation, which this book only summarizes (chapter 20).

Glossary

Term	What it is
access	what a person (or a conversation) can do in the business; it is the ceiling
agent	the artificial intelligence that fills a role
approval rule	guidance that tells a role what to ask about before acting
approvals ledger	one entry per approval, with the question, the person's words and the actions it covers
autonomy level	what a role can do on its own and what needs a person, depending on whether it can be undone without anyone noticing
blueprint	the common, versioned definition of how every business factory works
browser profile	the saved logins of a browser connection, one per site; conversations use instances that do not modify it
business definition	the record of how the business operates; the source of truth
business factory	the agents of a business or of an independent professional's practice, the place where they work and the rules that organize their work
ceiling	how far access reaches; nothing goes beyond it
channel	a platform where a role serves people from outside, through tools
connection	the way an agent reaches a system; it belongs to the role or to a person
consent	a person's explicit agreement for their own outside assistant to act on their behalf
conversation	where the business factory's work happens; it always belongs to a role
coordinating role	the top role of the business factory; it routes what crosses areas
copy (of the business factory)	each person's business factory, with